

**wall-mounted cooker hood, 60 cm,  
Stainless steel  
DWW06D650B**



**D**

**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

- An impressive extraction rate of 650 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.
- For fast and effective extraction, the intensive speed setting removes strong kitchen odours quickly and effectively.

**Technical Data**

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-864/582-974
Height of product, without chimney (mm) :	90
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	14.724
Type of control :	mechanical
Maximum output air extraction (m <sup>3</sup> /h) :	420
Boost position output recirculating (m <sup>3</sup> /h) :	380
Maximum output recirculating air (m <sup>3</sup> /h) :	280
Boost position air extraction (m <sup>3</sup> /h) :	650
Number of lights :	2
Noise level (dB(A) re 1 pW) :	59
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242002624815
Connection Rating (W) :	260
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Wall-mounted

**Optional accessories**

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ5326 : Active carbon filter
- DHZ6550 : Brushed steel back panel
- DHZ6551 : Brushed steel back panel
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6200 : CleanAir Recirculation Kit



## **wall-mounted cooker hood, 60 cm, Stainless steel DWW06D650B**

**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

---

### **Design**

- 60 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- Brushed steel canopy and chimney section

### **Features**

- Push button control for extractor speeds and light
- 3 power levels & intensive setting
- 2 x
- 2 metal grease filter cassettes

### **Performance/technical information**

- Easy installation system
- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591  $\varnothing$  15 cm:
  - max. Normal use 430 m<sup>3</sup>/h
  - Intensive 650 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
  - Max. normal use: 57 dB(A) re 1 pW (43 dB(A) re 20  $\mu$ Pa sound pressure)
  - Intensive: 67 dB(A) re 1 pW (53 dB(A) re 20  $\mu$ Pa sound pressure)
- Extractor hose 120mm
- Recirculating kit DHZ5325
- Dimensions recirculating with CleanAir module (HxWxD):
  - 654 x 600 x 500 mm - mounting with outer chimney
  - 774-1104 x 600 x 500 mm - mounting with telescopic chimney