

Series 4, free-standing fridge-freezer with freezer at bottom, 203 x 60 cm, Stainless steel look KGN39VLEAG





Included accessories 3 x egg tray 1 x ice cube tray with lid

I X ICE CUDE tray with he

NoFrost bottomfreezer: no need to defrost your freezer

- VitaFresh: keeps food fresh for longer in climate controlled drawers at near 0°C.
- LED lighting with soft start, lasts for the lifetime of the appliance.
- Automatic super freezing: optimal for freezing smaller food loads faster whilst protecting your frozen items from defrosting
- **EasyAccess Shelf:** pull-out glass shelf gives you better access to the contents of your fridge.
- **2 cooling circuits:** separately controllable refrigerator and freezer compartments prevents odour transfer.

Technical Data

A ↑ G

> Energy Efficiency Class: E Average annual energy consumption in kilowatt hour per year (kWh/a): 238 kWh/annum Sum of volume of frozen compartments: 89 l Sum of volume of chill compartments: 279 l Airborne acoustical noise emissions : 39 dB(A) re 1 pW Airborne acoustical noise emission class: C Built-in / Free-standing: Free-standing Door panel options: Not possible Height: 2030 mm Width of the appliance: 600 mm Depth: 660 mm Net weight: 77.2 kg Connection Rating: 100 W Fuse protection: 10 A Door hinge: Right reversible Frequency: 50-60 Hz Length electrical supply cord: 240 cm Number of compressors: 1 Number of independent cooling systems: 2 Interior ventilator: No Reversible Door Hinge: Yes Number of Adjustable Shelves in fridge compartment: 3 Shelves for Bottles: Yes Installation typology: N/A





Series 4, free-standing fridge-freezer with freezer at bottom, 203 x 60 cm, Stainless steel look KGN39VLEAG

NoFrost bottomfreezer: no need to defrost your freezer

- KGN39VLEAG
- No Frost, Fridge freezer
- Cambered Door, High-door design Stainless steel look

Design features

- Stainless steel look doors and Pearl grey (VZF 07127) side panels
- Integrated vertical handle Integrated vertical handle
- Right hinged door, reversible door
- Separate, electronic temperature control with LED display

Food freshness system

- Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity

Key features - Fridge section

- 1 VitaFresh drawer with humidity control Fruits and vegetables retain vitamins and stay fresh for longer
- ChillerBox recommended storage area for meat and fish MultiAirflow system - improves circulation of air around the fridge
- Bright interior LED fridge light
- 5 safety glass shelves (3 height adjustable)
- Door shelves in fridge door: 1 large and 3 small
- SuperCool function
- Bottle rack

Key features - Feezer section

- No Frost, never have to defrost ever again
- 3 freezer drawers
- SuperFreeze functions with automatic deactiviation
- Calendar frozen food
- Freezer malfunction warning signal: optical and acoustical warning system

Additional features

- Optical and acoustic door open alarm
- 3 x egg tray, 1 x ice cube tray

Dimension and installation


- Connection value 100 W
- 220 240 V
- Height adjustable front feet
- Dimensions: 203 cm H x 60 cm W x 66 cm D
- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- To achieve the declared energy consumption, the distanceholders have to be used. As a result, the appliance depth increases by about 3.5 cm. The appliance used without the distance holder is fully functional, but has a slightly higher energy consumption.


Performance and Consumption

- EU19 EEK D: E
- Total Volume : 368 l
- Net Fridge Volume : 279 l
- Net Freezer Volume : 89 l
- Freezing capacity 24h : 10 kg
- Annual Energy Consumption: 238 kWh/a
- Climate Class: SN-T
- EU19_Fast freezer facility_D: yes
- Noise Level : 39 dB
- Temperature rise time : EU19_Temperature rise time_D: 13 H



Series 4, free-standing fridge-freezer with freezer at bottom, 203 x 60 cm, Stainless steel look KGN39VLEAG





In models with vertical integrated handles, in order to open easily, a minimum distance of 65 mm is needed.

measurements in mm