

Series 4, free-standing fridge-freezer with freezer at bottom, 203 x 60 cm, Stainless steel look KGN39VLEBG











Included accessories

3 x egg tray 1 x ice cube tray

NoFrost bottomfreezer: no need to defrost your freezer

- VitaFresh: keeps food fresh for longer in climate controlled drawers at near 0°C.
- LED lighting with soft start, lasts for the lifetime of the appliance.
- Automatic super freezing: optimal for freezing smaller food loads faster whilst protecting your frozen items from defrosting
- EasyAccess Shelf: pull-out glass shelf gives you better access to the contents of your fridge.
- 2 cooling circuits: separately controllable refrigerator and freezer compartments prevents odour transfer.

Technical Data

A ↑ G

Energy Efficiency Class: E

Average annual energy consumption in kilowatt hour per year

(kWh/a): 238 kWh/annum

Sum of volume of frozen compartments: 89 I Sum of volume of chill compartments: 279 I

Airborne acoustical noise emissions: 39 dB(A) re 1 pW

Airborne acoustical noise emission class: C Built-in / Free-standing: Free-standing Door panel options: Not possible

Height: 2030 mm

Width of the appliance: 600 mm

Depth: 660 mm

Net weight: 80.0 kg

Connection Rating: 100 W

Fuse protection: 10 A

Door hinge: Right reversible

Frequency: 50-60 Hz

Length electrical supply cord: 240 cm

Number of compressors: 1

Number of independent cooling systems: 2

Interior ventilator: No Reversible Door Hinge: Yes

Number of Adjustable Shelves in fridge compartment: 3

Shelves for Bottles: Yes Installation typology: N/A





Series 4, free-standing fridge-freezer with freezer at bottom, 203 x 60 cm, Stainless steel look KGN39VLEBG

NoFrost bottomfreezer: no need to defrost your freezer

- KGN39VLEBG
- No Frost, Fridge freezer
- Cambered Door, High-door design Stainless steel look

Design features

- Stainless steel look doors and Pearl grey (VZF 07127) side panels
- Integrated vertical handle Integrated vertical handle
- Right hinged door, reversible door
- Separate, electronic temperature control with LED display

Food freshness system

- Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity

Key features - Fridge section

- 1 VitaFresh drawer with humidity control Fruits and vegetables retain vitamins and stay fresh for longer
- ChillerBox recommended storage area for meat and fish MultiAirflow system - improves circulation of air around the fridge
- Bright interior LED fridge light
- 5 safety glass shelves (3 height adjustable)
- Door shelves in fridge door: 1 large and 3 small
- SuperCool function
- Bottle rack

Key features - Feezer section

- No Frost, never have to defrost ever again
- 3 freezer drawers
- SuperFreeze functions with automatic deactiviation
- Calendar frozen food
- Freezer malfunction warning signal: optical and acoustical warning system

Additional features

- Optical and acoustic door open alarm
- 3 x egg tray, 1 x ice cube tray

Dimension and installation

- Connection value 100 W
- 220 240 V
- Height adjustable front feet
- Dimensions: 203 cm H x 60 cm W x 66 cm D
- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- To achieve the declared energy consumption, the distanceholders have to be used. As a result, the appliance depth increases by about 3.5 cm. The appliance used without the distance holder is fully functional, but has a slightly higher energy consumption.

Performance and Consumption

- EU19_EEK_D: E

- Total Volume: 368 I

- Net Fridge Volume : 279 l

- Net Freezer Volume : 89 l

- Freezing capacity 24h: 10 kg

- Annual Energy Consumption: 238 kWh/a

- Climate Class: SN-T


- EU19_Fast freezer facility_D: yes


- Noise Level: 39 dB


- Temperature rise time : EU19_Temperature rise time_D: 13 H



Series 4, free-standing fridge-freezer with freezer at bottom, 203 x 60 cm, Stainless steel look KGN39VLEBG







Dimension A:

In models with vertical integrated handles, in order to open easily, a minimum distance of 65 mm is needed.

measurements in mm