

## Series 8, built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm, flat hinge KIF86PFE0









#### Optional accessories

KSZ10020 Bottle Rack KSZGGM00 Butter box

# Built-in bottom freezer combination with VitaFresh pro: thanks to ideal storage conditions your food stays vitamin-rich and fresh up to 3 times longer.

- VitaFresh pro: keeps food fresh for longer thanks to optimal climate control and +0°C technology.
- LED lighting: all your items in perfect view.

A ↑ G

- VarioZone: more flexibility due to variable-use glass shelves and drawers in the freezer compartment.
- **Big Box drawer**: easily stack food containers and store larger items in your freezer.
- Vario Shelf: easily store large items with this split, sliding shelf.

### **Technical Data** Energy Efficiency Class<sup>1</sup>: ..... E Average annual energy consumption in kilowatt hour per year (kWh/a): ......252 kWh/annum Sum of volume of frozen compartments: ...... 67 l Sum of volume of chill compartments: ...... 156 l Airborne acoustical noise emission class: ......C Width of the appliance: ......558 mm Required niche size for installation (HxWxD): ... 1775 x 560 x 550 mm Net weight: ......70.1 kg Connection rating: ...... 90 W Fuse protection: ......10 A Door hinge: ...... Right reversible Frequency: ...... 50 Hz Number of compressors: ......1 Number of independent cooling systems: ......2 Interior ventilator: ...... No Frost free system: ..... Fridge and freezer Installation typology: ...... Integrated



Scale of Energy Efficiency Classes from A to G



Series 8, built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm, flat hinge KIF86PFE0

Built-in bottom freezer combination with VitaFresh pro: thanks to ideal storage conditions your food stays vitamin-rich and fresh up to 3 times longer.

- easy Installation

#### Functions

- Electronic control for fridge and freezer with LED display

#### **Design features**

- NoFrost freezer, never have to defrost ever again
- Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity
- Optical and acoustical door open warning

#### Food freshness system

- FreshSense Constant temperature control by intelligent sensor technology
- 1 VitaFresh pro 0°C drawer with humidity control fruits and vegetables stay vitamin-rich and fresher for longer.
- Vario Zone removable safety glass shelves for extra space!

### Key features - Fridge section

- Bright interior LED fridge light
- Holiday mode saves energy when you're away a longer period of time
- SuperCool function
- 2 door trays, including 1x dairy compartment
- 3 safety glass shelves (2 height adjustable)

### Key features - Feezer section

- 3 transparent freezer drawers, including 1 BigBox
- 1 x ice cube tray,
- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.

#### Dimension and installation

- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D
- Dimensions: 177.2 cm H x 55.8 cm W x 54.5 cm D
- Right hinged door, reversible door
- Connection value 90 W
- 220 240 V

#### Additional features


#### **Performance and Consumption**


- EU19\_EEK\_D: E
- Total Volume : 223 l
- Net Fridge Volume: 156 l
- Net Freezer Volume : 67 l
- Freezing capacity 24h : 7 kg
- Annual Energy Consumption: 252 kWh/a
- Climate Class: SN-ST

- Noise Level : 36 dB
- Temperature rise time : EU19\_Temperature rise time\_D: 8 H



## Series 8, built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm, flat hinge KIF86PFE0





#### Maximal permissible weight of the unit fronts


Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges  $\Delta$  Weight  $\Delta$ : Appliance door height including hinges in mm


B: Undamped hinge, unit front in kg


C: Damped hinge, unit front in kg

 $\mathbf{D}\text{:}$  Additional possible load in kg with heavy load kit


Α	В	С	D
1500-1750	22	22	
720-1400	19	19	B+5 / C+5
A1	15	19	
Δ2	15	10	1







measurements in mm Recommended gap dimensions for flat hinges



F	R	X
16-19	0-3	2.5
20	0-1	3
	2-3	2.5
21	0-1	3
	2-3	2.5
22	0	4
	1	3.5
	2-3	3

The specified unit door dimensions are valid for a door gap of 4 mm.

measurements in mm

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.