

Series 4, Gas hob, 60 cm, Stainless steel PGP6B5B90



HEZ298105 Simmer plate
HEZ298115 Small pot support

The gas hob with front-mounted controls: the desired cooking zones can be conveniently operated from the front.

- **Continuous cast-iron pan supports:** for maximum stability.
- **Biomethane-ready:** your gas hob can also be powered with renewable biomethane gas.
- **Ergonomic control knobs with raised center for precise adjustments.**
- **Surface colour: elegant stainless-steel design.**
- **Stainless steel design: The seamless, one-piece stainless steel design makes cleaning simple**

Product name/family:gas hob w integrated controls
Built-in / Free-standing: Built-in
Energy input:Gas
Number of cooking zones:4
Type of control setting devices: sword knobs
Required niche size for installation (HxWxD): 45 x 560-562 x 480-492 mm
Width of the appliance:582 mm
Dimensions: 53x582x520 mm
Dimensions of the packed product (HxWxD): 168 x 798 x 596 mm
Net weight:9.6 kg
Gross weight: 10.5 kg
Residual heat indicator: without
Location of control panel: Front
Basic surface material: Stainless steel
Color of surface: Stainless steel
Length electrical supply cord: 100.0 cm
EAN code:4242005119318
Gas connection rating: 7500 W
Fuse protection:3 A
Voltage: 220-240 V
Frequency: 50; 60 Hz



4 242005 119318

Series 4, Gas hob, 60 cm, Stainless steel PGP6B5B90

**The gas hob with front-mounted controls:
the desired cooking zones can be
conveniently operated from the front.**

Design

- Stainless steel surface
- Cast iron pan supports

Usage convenience

- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 gas burners
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: High-speed burner up to 3 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 582 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.5 KW

Series 4, Gas hob, 60 cm, Stainless steel
PGP6B5B90

