


**Series 4, Gas hob, 75 cm, Stainless steel
PGQ7B5B90**



HEZ298105 Simmer plate
HEZ298108 Wok ring
HEZ298115 Small pot support

**The gas hob with front-mounted controls:
the desired cooking zones can be
conveniently operated from the front.**

- Dual ring burner has a wide range of power from a high heat dual flame down to one small simmer flame.

Product name/family:gas hob w integrated controls
Built-in / Free-standing: Built-in
Energy input:Gas
Number of cooking zones:5
Type of control setting devices: sword knobs
Required niche size for installation (HxWxD): 45 x 560-562 x 480-492 mm
Width of the appliance: 750 mm
Dimensions: 53x750x520 mm
Dimensions of the packed product (HxWxD): 168 x 798 x 596 mm
Net weight: 12.9 kg
Gross weight: 14.5 kg
Residual heat indicator: without
Location of control panel: Front
Basic surface material: Stainless steel
Color of surface: Stainless steel
Length electrical supply cord: 150.0 cm
EAN code:4242005096930
Gas connection rating: 10800 W
Fuse protection:3 A
Voltage: 220-240 V
Frequency: 50; 60 Hz



Series 4, Gas hob, 75 cm, Stainless steel PGQ7B5B90

**The gas hob with front-mounted controls:
the desired cooking zones can be
conveniently operated from the front.**

Design

- Stainless steel surface
- Cast iron pan supports

Usage convenience

- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 gas burners
- Left front: economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: wok burner up to 3.3 KW (depending on gas type)
- Right rear: High-speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 750 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1.5 m
- Connected load: 10.8 KW

Series 4, Gas hob, 75 cm, Stainless steel
PGQ7B5B90

