

**Serie | 4, gas hob, 60 cm, Tempered glass
PNP6B6B80**



**The gas hob with front-mounted controls:
the desired cooking zones can be
conveniently operated from the front.**

- **Continuous steel pan supports:** for maximum stability.
- **Sword knobs:** for an ergonomic control.
- **Surface colour:** elegant black tempered-glass design.
- **Tempered Glass:** for strength and aesthetic.
- **Stainless steel cooking surface:** easily accessible and quick to clean.

Technical Data

Product name/family :	gas hob w integrated controls
Construction type :	Built-in
Energy input :	Gas
Total number of positions that can be used at the same time :	4
Type of control setting devices :	sword knobs
Required niche size for installation (HxWxD) :	45 x 560-562 x 480-492
Width of the appliance :	590
Dimensions :	45 x 590 x 520
Dimensions of the packed product (HxWxD) (mm) :	141 x 651 x 578
Net weight (kg) :	10.606
Gross weight (kg) :	11.5
Residual heat indicator :	without
Location of control panel :	Hob front
Basic surface material :	Tempered glass
Color of surface :	Black
Color of frame :	Black
Approval certificates :	CE, Eurasian
Length electrical supply cord (cm) :	100
EAN code :	4242002928036
Electrical connection rating (W) :	1
Gas connection rating (W) :	7500
Current (A) :	3
Voltage (V) :	220-240
Frequency (Hz) :	60; 50



4 242002 928036

Serie | 4, gas hob, 60 cm, Tempered glass PNP6B6B80

**The gas hob with front-mounted controls:
the desired cooking zones can be
conveniently operated from the front.**

Design

- Black Tempered glass
- frameless

Special features

- Design co-ordinated control dials
- Ignition via control dials
- enamelled pan supports

Power and size

- 4 gas burners
- Left rear: Standard burner 1.75 KW
- Right rear: High-speed burner 3 KW
- Left front: Standard burner 1.75 KW
- Right front: Economy burner 1 KW

Safety Features

- Flame failure safety device
- Pre-set for natural gas. Also usable for Nat gas L/LL
G25/20mbar(DE)
NG H/E 20mbar, E+ 20/25mbar
Natural gas H 25 mbar (HU)
Natural gas L 25 mbar (NL)
Liquid gas G30,31 28-30/37mbar
Liquid gas G30 37 mbar (PL)
Liquid gas 50 mbar
. For the use of these gas types nozzles need to be changed.
Please check if the required nozzles are included (see
Accessories).

Technical information

- Power cord length 100 cm

Accessories

- Nozzle set for LPG jets included. Connection to 28-30/37
mbar bottled gas. Nozzles for all other gas types can be
ordered via the customer service.

**Serie | 4, gas hob, 60 cm, Tempered glass
PNP6B6B80**

