Serie | 4, induction hob, 60 cm, PUG611BF5B

The Induction hob: Faster than gas and ceramic hobs, induction is easier to clean and more energy efficient.

- Plug & Play: Plugs easily into the socket.
- **TouchSelect:** Selection of the desired cooking zone and easy setting of the desired power level.
- **Induction:** Fast, precise cooking, easy cleaning and low energy consumption.
- PowerBoost: Up to 50% more power for faster heating.
- Timer with switch-off function: Turns off the assigned cooking zone after the set time.

Technical Data

Product name/family: Cooking zone ceramic Construction type: Built-in Energy input: Electric Total number of positions that can be used at the same time: 4

Required niche size for installation (HxWxD) :

51 x 560-560 x 490-500

Appliance Width (mm): 592
Dimensions of the product (mm): 51 x 592 x 522

Dimensions of the packed product (HxWxD) (mm):

126 x 753 x 608

Net weight (kg): 10.585 Gross weight (kg): 11.7 Residual heat indicator: Separate Location of control panel: Hob front Basic surface material: Ceramic Color of surface: Black AENOR, CE Approval certificates: Length electrical supply cord (cm): 110

EAN code: 4242005151127
Electrical connection rating (W): 3000
Voltage (V): 220-240
Frequency (Hz): 50



Optional accessories

HEZ9SE030 : Set of 2 pots and 1 pan

Serie | 4, induction hob, 60 cm, PUG611BF5B

The Induction hob: Faster than gas and ceramic hobs, induction is easier to clean and more energy efficient.

Design

- Frameless design

Speacial features

- PowerBoost function for all zones
- 4 induction cooking zones
- TouchControl
- Digital display
- Timer for all zones Timer - shows how long the cooktop is in use
- ReStart function
- QuickStart function
- Power and size:
- Cooking zones: 1 x Ø 145 mm, 1.4 KW (max. Power levels 2.2 KW) Induction; 1 x Ø 180 mm, 1.8 KW (max. Power levels 3.1 KW) Induction; 1 x Ø 145 mm, 1.4 KW (max. Power levels 2.2 KW) Induction; 1 x Ø 180 mm, 1.8 KW (max. Power levels 3.1 KW) Induction
- Variable 17-stage power settings for each zone

Safety Features

- 2 stage residual heat indicator for each zone
- Main on/off switch
- Automatic pan recognition sensor Safety cut-out switch-off Control panel lock

Technical information

- Measurement: (H/W/D) 51 x 592 x 522 mm
- Installation dimensions: (ID/W/D) 51 mm x 560 mm x 490 mm
- Min. worktop thickness: 30 mm
- Connected load: 3 kW
- Connection cable 110 cm
- connected to terminal block
- This hob is equipped with a UK 3 pin plug for an easy plug & play installation. The plug limits the maximum power output to 3 kW. For higher power output, please select a hob without plug and ensure installation is carried out by a qualified electrician.