

**Serie | 2, free-standing dishwasher, 60 cm, Stainless steel, lacquered
SMS25EI00G**



- **ExtraDry:** extra drying option for difficult-to-dry loads.
- **Glass 40°C:** protective programme for gently cleaning and drying glasses.
- **VarioDrawer:** 3rd level loading for cutlery and smaller kitchen utensils.
- **Rackmatic:** even more adjustment options and thus maximum flexibility.
- **Rackmatic:** top basket adjustable on three levels offers additional space, especially for tall dishes.

Technical Data

Energy Efficiency Class (Regulation (EU) 2017/1369):	E
Energy Consumption for 100 cycles Eco Programme (EU 2017/1369):	94
Maximum number of place settings (EU 2017/1369):	13
The water consumption of the eco programme in liters per cycle (EU 2017/1369):	9.5
Programme duration (EU 2017/1369):	3:30
Airborne acoustical noise emissions (EU 2017/1369):	48
Airborne acoustical noise emission class (EU 2017/1369):	C
Built-in / Free-standing:	Free-standing
Height of removable worktop (mm):	30
Dimensions of the product (HxWxD):	845 x 600 x 600
Approval certificates:	CE, VDE
Depth with open door 90 degree (mm):	1155
Adjustable feet:	Yes - all
Maximum adjustability feet (mm):	20
Net weight (kg):	49.042
Gross weight (kg):	50.3
Connection Rating (W):	2400
Current (A):	10
Voltage (V):	220-240
Frequency (Hz):	50; 60
Length electrical supply cord (cm):	175
Plug type:	GB plug
Length inlet hose (cm):	150
Length outlet hose (cm):	190
EAN code:	4242005028436
Installation typology:	Built-under



4 242005 028436

Serie | 2, free-standing dishwasher, 60 cm, Stainless steel, lacquered SMS25EI00G

Performance

- Energy Efficiency Class¹: E
- Energy² / Water³: 94 kWh / 9.5 litres
- Capacity: 13 place settings
- Programme duration⁴: 3:30 (h:min)
- Noise level: 48 dB(A) re 1 pW
- Noise Efficiency Class: C

Programmes/functions

- 5 programmes: Intensive 70 °C, Eco, Glass 40 °C, Quick, Prerinse
- 2 special options: VarioSpeedPlus, Extra Dry

Flexible design elements

- Vario basket system
- VarioDrawer - loading of cutlery on 3rd level
- 3 stage Rackmatic height-adjustable top basket
- 2 foldable plate racks in bottom basket
- Upper rack cup shelf

Innovations and technology

- Heat exchanger - Hygienic and efficient drying
- DosageAssist detergent dispenser
- EcoSilence BLDC drive
- Automatic detergent detection
- Load Sensor

Design features

- Time delay (3, 6 or 24 hours)
- Leak protection system
- LED salt refill indicator, LED rinse aid refill indicator
- Self-cleaning filter system with 3 piece corrugated filter
- Child safety - Childproof door lock.
- Dimensions (HxWxD): 84.5 x 60 x 60cm

¹ Scale of Energy Efficiency Classes from A to G

² Energy consumption in kWh per 100 cycles (in programme Eco 50 °C)

³ Water consumption in litres per cycle (in programme Eco 50 °C)

⁴ Duration of programme Eco 50 °C