

**Serie | 4, Wall mounted hoods, 90 cm
DEE928PIN**

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- **Extraction rate:** at 1000 m³/h, it quickly ensures optimal kitchen air quality, with connect pipe:180 mm inner diameter/195 mm outer diameter
- **LED lighting:** for optimal, energy-efficient illumination of the hob.
- **Especially quiet:** high performance at just 71 dB(A)(sound power level), 57 dB(A)(sound pressure level).
- **High efficiency grease filtration system:** European style baffle filter system

Technical Data

Typology :	Chimney
Length electrical supply cord (cm) :	150
Net weight (kg) :	24.586
Type of control :	Electronic
Number of speed settings :	3-stage
Number of lights :	2
Diameter of air outlet (mm) :	180
Grease filter material :	Washable stainless steel
Odour filter :	No
Operating Mode :	Convertible
Optional accessories :	DHZ5705, DHZ5706
Type of lamps used :	LED
Connection Rating (W) :	206
Voltage (V) :	220-240
Frequency (Hz) :	50
Installation typology :	Wall-mounted
Material body :	Stainless steel
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	26.96 x 29.68 x 39.17
Net weight (lbs) :	54
Gross weight (lbs) :	82
Motor location :	Integrated motor in hood chimney
No-return airflow flap :	No
Length electrical supply cord (cm) :	150
Dimensions of the product, with chimney (if exists) (mm) :	707-1195 x 895.0 x 530.0
Dimensions of the packed product (HxWxD) (mm) :	685 x 754 x 995
Net weight (kg) :	24.586
Gross weight (kg) :	37.0



Serie | 4, Wall mounted hoods, 90 cm DEE928PIN

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

Design:

- 90 cm Pyramidal slimline hood
- Push buttons

Features:

- Operation mode hoods: Ducted/Recirculating operation
- Max. extraction rate: 1000 m³/h
- Max. noise level: 71 dB
- Total power of motors: 200 W
- 3 high efficiency Baffle filters
- Illumin type - kind of lamps: LED 3W
- Stainless steel hood which is easy to clean
- Multi-stage fan regulation

Dimensions:

- Exhaust air dimensions (HxWxD): 707-1075 mm x 89.5 cm x 53 cm
- Recirculating dimensions (HxWxD): 707-1195 mm x 89.5 cm x 53 cm
- Ducting connection diameter: 18 cm
- Connecting cable 150 cm