

**Serie | 4, Wall mounted hoods, 90 cm,  
Stainless steel  
DEE936BIN**



**The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.**

- **Extraction rate:** at 960 m<sup>3</sup>/h, it quickly ensures optimal kitchen air quality, with connect pipe:180 mm inner diameter/195 mm outer diameter
- **Especially quiet:** high performance at just 58 dB(A)(sound pressure level),72 dB(A)(sound power level)
- **Halogen lighting:** for optimal, energy-efficient illumination of the hob.
- **High efficiency grease filtration system:** European style baffle filter system

**Technical Data**

Typology :	Chimney
Length electrical supply cord (cm) :	150
Net weight (kg) :	24.586
Type of control :	Electronic
Number of speed settings :	4-stage
Number of lights :	2
Diameter of air outlet (mm) :	180
Grease filter material :	Washable stainless steel
Odour filter :	No
Operating Mode :	Convertible
Optional accessories :	LZ57050, LZ57051
Type of lamps used :	Halogen
Total power of the lamps (W) :	40
Connection Rating (W) :	250
Voltage (V) :	220-240
Frequency (Hz) :	50
Installation typology :	Wall-mounted
Material body :	Stainless steel
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	26.96 x 29.68 x 39.17
Net weight (lbs) :	54
Gross weight (lbs) :	82
Motor location :	Integrated motor in hood chimney
No-return airflow flap :	No
Length electrical supply cord (cm) :	150
Dimensions of the product, with chimney (if exists) (mm) :	664-1154 x 895.0 x 530.0
Dimensions of the packed product (HxWxD) (mm) :	685 x 754 x 995
Net weight (kg) :	24.586
Gross weight (kg) :	37.0



**Serie | 4, Wall mounted hoods, 90 cm,  
Stainless steel  
DEE936BIN**

**The wall-mounted chimney hood: mount it  
on the wall, giving you complete freedom in  
your kitchen planning.**

---

**Design:**

- Box slimline common design hood
- Push buttons

**Features:**

- Operation mode hoods: Ducted/Recirculating operation
- Low volt halogen spot 20W
  
- Stainless steel hood which is easy to clean
- Multi-stage fan regulation
- 3 high efficiency Baffle filters
- Integrative chimney, easy to clean
- Total power of motors: 210 W
- Max. extraction rate: 960 m<sup>3</sup>/h
- Noise level is 58 dB

**Dimensions:**

- Exhaust air dimensions (HxWxD): 664-1034 mm x 90 cm x 53 cm
- Recirculating dimensions (HxWxD): 664-1154 mm x 90 cm x 53 cm
- Ducting connection diameter: 18 cm
- Connecting cable 150 cm

**Total Connected load: 250 W**