

**Series 6, island cooker hood, 90 cm,
Stainless Steel
DIB98JQ50I**



DHZ5346 Standard odor filter (replacement), DHZ5385 Standard recirculation kit, DIZ2CB1I4 Clean Air Standard recirculation kit, DIZ2CX5C6 Clean Air Plus recirc. kit external, DIZ2FX5D1 Long Life recirculation kit external, DZZ0XX0P0 Long Life odor filter (replacement), DZZ1XX1B6 Clean Air Plus odor filter (replacement), DZZ2CB1B4 Clean Air Standard odor filter (repl.), DHZ1246 Chimney extension 1100 mm, DHZ1251 Extension for mounting kit 500 mm, DHZ1253 Extension for mounting kit 1000 mm, DHZ1256 Chimney extension 1600 mm, DHZ1231 Adapter for roof inclination left/right, DHZ1241 Adapter for roof inclination front/back

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- **PerfectAir sensor:** enjoy quieter, odour-free cooking.
- **Extra quiet:** maximum extractor performance with minimal noise.
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **For fast and effective extraction, the intensive speed setting removes strong kitchen odours quickly and effectively.**

Typology:Island/Ceiling
 Length electrical supply cord: 130.0 cm
 Height of the chimney: 698-878/698-998 mm
 Height of product, without chimney: 46 mm
 Net weight:30.1 kg
 Type of control:Electronic
 Number of speed settings:3-stage + 2 intensive
 Max. air extraction:445 m³/h
 Boost position output recirculating:457 m³/h
 Max. air recirculation: 353 m³/h
 Boost position air extraction: 867 m³/h
 Number of lights: 4
 Noise level:54 dB(A) re 1pW
 Diameter of air outlet: 120 / 150 mm
 Grease filter material: Washable stainless steel
 Odour filter: No
 Operating Mode:Convertible
 Optional accessories: ..DHZ5346, DHZ5385, DIZ2CB1I4, DIZ2CX5C6, DIZ2FX5D1, DZZ0XX0P0, DZZ1XX1B6, DZZ2CB1B4, DHZ1246, DHZ1251, DHZ1253, DHZ1256, DHZ1231, DHZ1241
 Type of lamps used: LED
 Grease filter type: Multilayer cassette
 Connection rating: 166 W
 Fuse protection:10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: India plug (6 Ampere)
 Installation typology: Island
 Material body: Stainless steel
 Plug type: India plug (6 Ampere)
 Dimensions of the product, with chimney (if exists) (in):x x
 Dimensions of the packed product: 32.67 x 24.01 x 40.94
 Net weight:66.000 lbs
 Gross weight: 89.000 lbs
 Motor location:Integrated motor in hood chimney
 No-return airflow flap:
 Length electrical supply cord: 130.0 cm
 Dimensions of the product, with chimney (if exists): 744-1044 x 898.0 x 600.0 mm
 Dimensions of the packed product (HxWxD): ... 830 x 610 x 1040 mm
 Net weight:30.1 kg
 Gross weight: 40.5 kg
 Delay Shut off modes: 10 min



Series 6, island cooker hood, 90 cm, Stainless Steel DIB98JQ50I

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Total Connected load: 166 W
- Connecting cable 130 cm
- Voltage: 220 - 240 V

* In accordance with the EU-Regulation No 65/2014

Design

- 90 cm stainless steel Box design hood
- Box design
- Ceiling
- Touch control (3 speeds plus 2 intensive) with lightline

Performance

- 3 speeds plus 2 intensive
- Extraction rate according to EN 61591 \varnothing 15 cm:
- max. Normal use: 445 m³/h
- Intensive: 867 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
- Max. normal use: 54 dB(A) re 1 pW (41 dB(A) re 20 μ Pa sound pressure)
- Intensive: 69 dB(A) re 1 pW (56 dB(A) re 20 μ Pa sound pressure)
- Extraction rate in recirculation mode:
- Max. normal use: 371 m³/h
- Intensive: 513 m³/h
- Noise levels in recirculation mode:
- Max. normal use: 67 dB(A) re 1 pW (58 dB(A) re 20 μ Pa sound pressure)
- Intensive: 75 dB(A) re 1 pW (61 dB(A) re 20 μ Pa sound pressure)

Comfort

- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- easy to clean innerframe
- Air quality sensor
- Light dimmer function
- Softlight with dimmer function
- Efficient BLDC-technology
- 4 x 1.5W LED
- Light Intensity: 423 lux
- Colour Temperature: 3500 K
- Saturation display filter: grease- and charcoal filter
- Steel filter cover
- Additional noise reduction insulation
- Back-pressure flap: No
- Energy Efficiency Class: A+
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*

Technical Information

- Suitable for ducted or recirculating operation only
- Recirculation kit or clean air kit
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)

**Series 6, island cooker hood, 90 cm,
Stainless Steel
DIB98JQ50I**

