

**Serie | 4, island cooker hood, 90 cm,
clear glass
DIG098G50I**



**Ideal for contemporary kitchens – this hood
also complements any island hob in style
and performance.**

- **Extraction rate:** Optimal performance to keep your kitchen odour free in no time
- **LED-Illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- For fast and effective extraction, the intensive speed setting removes strong kitchen odours quickly and effectively.
- **Intensive speed setting with reset:** automatically resets the hood to normal speed setting
- Ducted or Non-ducted Options

Technical Data

Typology : Island/Ceiling

Approval certificates : not relevant

Height of product, without chimney : 340 mm

Net weight : 26.9 kg

Type of control : Electronic

Boost position output recirculating : 575.0 m³/h

Maximum output recirculating air : 545 m³/h

Boost position air extraction : 705 m³/h

Number of lights : 4

Diameter of air outlet : 120 / 150 mm

Grease filter material : Washable stainless steel

Odour filter : No

Operating Mode : Convertible

Delay Shut off modes : 30 min

Optional accessories : DHZ5477

Type of lamps used : LED

Total power of the lamps : 4 W

Voltage : 230 V

Frequency : 50 Hz

Installation typology : Island

Material body : Stainless steel

Approval certificates : not relevant

Dimensions of the product, with chimney (if exists) (in) : / x x

Dimensions of the packed product : 18.50 x 29.92 x 38.97

Net weight : 59.000 lbs

Gross weight : 81.000 lbs

Motor location : Integrated motor in hood chimney

No-return airflow flap : No

Dimensions of the product, with chimney (if exists) : x 900.0 x 700.0 mm

Dimensions of the packed product (HxWxD) : 470 x 760 x 990 mm

Net weight : 26.9 kg

Gross weight : 36.9 kg



4 242002 973579

**Serie | 4, island cooker hood, 90 cm, clear glass
DIG098G50I**

Ideal for contemporary kitchens – this hood also complements any island hob in style and performance.

Design

- Straight glass and box design for Ceiling mounting
- Brushed stainless steel and transparent glass screen
- Electronic touch control on black full width glass panel, on one side
- Chromed logo strip on the chimney
- Sleek White LED indication of settings

Key Functions

- Maximum extraction rate according to EN 61591: 705 m³/h
- Maximum blower performance: 745 m³/h (freeblowing)
- 4 fan speed settings (three plus intense)

Comfort

- 4 x 4 W LED lighting
- Intensive speed automatically switches back to previous setting after 10 minutes
- Double-layered, high grade stainless steel Baffle filters
- Noise level from 55 dB to 77 dB

Technical information

- For Ceiling mounting only
- Suitable for ducted or recirculating operation
- Dimensions of the product, with chimney (if exists) (HxWxD mm): 1000 x 900 x 700
- Minimum clearance to gas/electric cook top: 750 mm
- Length electrical supply cord: 150 cm
- Ducting connection: 150mm/120mm diameter

** In accordance with the EU-Regulation No 65/2014*

**Serie | 4, island cooker hood, 90 cm, clear
glass
DIG098G50I**

