

## Serie | 2, Wall mounted hoods, 90 cm, Stainless steel DKE908PIN



# The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- Extraction rate: at 860 m3/h, it quickly ensures optimal kitchen air quality, with connect pipe:160 mm inner diameter/175 mm outer diameter
- **Especially quiet:** high performance at just 55 dB(A)(sound pressure level),69 dB(A)(sound power level)
- **High efficency grease filtration system:** pyramid filter and oil collector system
- Halogen lighting: for optimal, energy-efficient illumination of the hob.

### Technical Data

Length electrical supply cord (cm) :150Height of the chimney (mm) :780Net weight (kg) :18.872Type of control :mechanicalNumber of speed settings :3-stageNumber of lights :2Diameter of air outlet (mm) :160Odour filter :NoOperating Mode :Air extraction onlyType of lamps used :HalogenTotal power of the lamps (W) :40Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :S95-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872Gross weight (kg) :18.872Gross weight (kg) :30.0	Typology :	Chimney
Net weight (kg) :18.872Type of control :mechanicalNumber of speed settings :3-stageNumber of lights :2Diameter of air outlet (mm) :160Odour filter :NoOperating Mode :Air extraction onlyType of lamps used :HalogenTotal power of the lamps (W) :40Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the product, with chimney (if exists) (in) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Length electrical supply cord (cm) :	150
Type of control :mechanicalNumber of speed settings :3-stageNumber of lights :2Diameter of air outlet (mm) :160Odour filter :NoOperating Mode :Air extraction onlyType of lamps used :HalogenTotal power of the lamps (W) :40Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Height of the chimney (mm) :	780
Number of speed settings :3-stageNumber of lights :2Diameter of air outlet (mm) :160Odour filter :NoOperating Mode :Air extraction onlyType of lamps used :HalogenTotal power of the lamps (W) :40Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Net weight (kg) :	18.872
Number of lights :2Diameter of air outlet (mm) :160Odour filter :NoOperating Mode :Air extraction onlyType of lamps used :HalogenTotal power of the lamps (W) :40Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Type of control :	mechanical
Diameter of air outlet (mm) :160Odour filter :NoOperating Mode :Air extraction onlyType of lamps used :HalogenTotal power of the lamps (W) :40Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the product, with chimney (if exists) (in) :/ x sDimensions of the product, with chimney (if exists) (in) :/ x sDimensions of the product, with chimney (if exists) (in) :/ x sDimensions of the product, with chimney (if exists) (in) :/ sNet weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Number of speed settings :	3-stage
Odour filter :NoOperating Mode :Air extraction onlyType of lamps used :HalogenTotal power of the lamps (W) :40Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Number of lights :	2
Operating Mode :Air extraction onlyType of lamps used :HalogenTotal power of the lamps (W) :40Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Diameter of air outlet (mm) :	160
Type of lamps used :HalogenTotal power of the lamps (W) :40Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Odour filter :	No
Total power of the lamps (W) :40Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Operating Mode :	Air extraction only
Connection Rating (W) :190Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Type of lamps used :	Halogen
Current (A) :10Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Total power of the lamps (W) :	40
Voltage (V) :220-240Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Connection Rating (W) :	190
Frequency (Hz) :50Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Current (A) :	10
Installation typology :Wall-mountedMaterial body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Voltage (V) :	220-240
Material body :Glass, Stainless steelDimensions of the product, with chimney (if exists) (in) :/ x xDimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Frequency (Hz) :	50
Dimensions of the product, with chimney (if exists) (in) : / x x Dimensions of the packed product (in) : 26.96 x 27.16 x 39.17 Net weight (lbs) : 42 Gross weight (lbs) : 66 Motor location : Integrated motor in hood body No-return airflow flap : No Length electrical supply cord (cm) : 150 Dimensions of the product, with chimney (if exists) (mm) : 595-880 x 895.0 x 530.0 Dimensions of the packed product (HxWxD) (mm) : 685 x 690 x 995 Net weight (kg) : 18.872	Installation typology :	Wall-mounted
Dimensions of the packed product (in) :26.96 x 27.16 x 39.17Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Material body :	Glass, Stainless steel
Net weight (lbs) :42Gross weight (lbs) :66Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Dimensions of the product, with chimney (if exists) (in) : $/ x x$	
Gross weight (lbs) : 66 Motor location : Integrated motor in hood body No-return airflow flap : No Length electrical supply cord (cm) : 150 Dimensions of the product, with chimney (if exists) (mm) : 595-880 x 895.0 x 530.0 Dimensions of the packed product (HxWxD) (mm) : 685 x 690 x 995 Net weight (kg) : 18.872	Dimensions of the packed product (in) : 26.96 x 27.16 x 39.17	
Motor location :Integrated motor in hood bodyNo-return airflow flap :NoLength electrical supply cord (cm) :150Dimensions of the product, with chimney (if exists) (mm) :595-880 x 895.0 x 530.0Dimensions of the packed product (HxWxD) (mm) :685 x 690 x 995Net weight (kg) :18.872	Net weight (lbs) :	42
No-return airflow flap : No Length electrical supply cord (cm) : 150 Dimensions of the product, with chimney (if exists) (mm) : 595-880 x 895.0 x 530.0 Dimensions of the packed product (HxWxD) (mm) : 685 x 690 x 995 Net weight (kg) : 18.872	Gross weight (lbs) :	66
Length electrical supply cord (cm) : 150 Dimensions of the product, with chimney (if exists) (mm) : 595-880 x 895.0 x 530.0 Dimensions of the packed product (HxWxD) (mm) : 685 x 690 x 995 Net weight (kg) : 18.872	Motor location : In	tegrated motor in hood body
Dimensions of the product, with chimney (if exists) (mm) : 595-880 x 895.0 x 530.0 Dimensions of the packed product (HxWxD) (mm) : 685 x 690 x 995 Net weight (kg) : 18.872	No-return airflow flap :	No
595-880 x 895.0 x 530.0 Dimensions of the packed product (HxWxD) (mm) : 685 x 690 x 995 Net weight (kg) : 18.872	Length electrical supply cord (cm) :	150
Dimensions of the packed product (HxWxD) (mm) :	Dimensions of the product, with chimney (if exists) (mm) :	
685 x 690 x 995 Net weight (kg) : 18.872	595-880 x 895.0 x 530.0	
Net weight (kg) : 18.872	Dimensions of the packed product (	HxWxD) (mm) :
	685 x 690 x 995	
Gross weight (kg) : 30.0	Net weight (kg) :	18.872
	Gross weight (kg) :	30.0





Serie | 2, Wall mounted hoods, 90 cm, Stainless steel DKE908PIN

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

#### Design:

- Design line: 90cm pyramid
- Rocker switches

## Features:

- Lamp power halogen light: 40 W
- Fan regulation: 3-stage
- Metal grease filter, oil collector
- Stainless steel hood
- Total power of the motors: 150 W
- Max. extraction rate: 860 m<sup>3</sup>/h
- Noise level: 55 dba

#### Dimensions:

- Appliance Dimensions (HXWXD): 595-880 mm X 90 cm X 53 cm
- Diameter pipe: 16 cm
- Connecting cable: 150 cm
- Total connected load: 190 W