

Series 8, wall-mounted cooker hood, 90 cm, Stainless steel DWB091K50



DHZ1223	Chimney extension 1000 mm
DHZ1233	Chimney extension 1500 mm
DHZ5345	Standard recirculation kit
DHZ5346	Standard odor filter (replacement)
DSZ5201	CleanAir active carbon filter spare part
DSZ6240	CleanAir Recirculation Kit
DZZ0XX0P0	Long Life odor filter (replacement)

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **For fast and effective extraction, the intensive speed setting removes strong kitchen odours quickly and effectively.**
- **Extraction rate: Optimal performance to keep your kitchen odour free in no time**
- **Intensive speed setting with reset: automatically resets the hood to normal speed setting**
- **Ducted or Non-ducted Options**

Typology:Wall-mounted
 Length electrical supply cord: 130.0 cm
 Height of the chimney: 582-908/582-1018 mm
 Height of product, without chimney: 46 mm
 Net weight: 26.6 kg
 Type of control:Electronic
 Number of speed settings:3-stage + 2 intensive
 Max. air extraction: 600 m³/h
 Boost position output recirculating:480.0 m³/h
 Max. air recirculation: 400 m³/h
 Boost position air extraction: 790 m³/h
 Number of lights: 3
 Noise level:66 dB(A) re 1pW
 Diameter of air outlet: 150 / 120 mm
 Grease filter material: Washable stainless steel
 Odour filter: No
 Operating Mode: Convertible
 Optional accessories: DHZ1223, DHZ1233, DHZ5345, DHZ5346, DSZ5201, DSZ6240, DZZ0XX0P0
 Type of lamps used: LED
 Total power of the lamps: 9 W
 Grease filter type: Multilayer
 Clean filter reminders:Yes
 Connection rating: 269 W
 Fuse protection:10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: Gardy plug w/ earthing
 Installation typology:Wall-mounted
 Material body: Stainless steel
 Plug type: Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in):x x
 Dimensions of the packed product: 23.03 x 25.59 x 38.18
 Net weight:59.000 lbs
 Gross weight: 60.000 lbs
 Motor location: Integrated motor in hood chimney
 No-return airflow flap: Yes
 Length electrical supply cord: 130.0 cm
 Dimensions of the product, with chimney (if exists): 628-1064 x 900.0 x 500.0 mm
 Dimensions of the packed product (HxWxD): 585 x 650 x 970 mm
 Net weight:26.6 kg
 Gross weight: 27.1 kg



Series 8, wall-mounted cooker hood, 90 cm, Stainless steel DWB091K50

**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom
in your kitchen planning.**

Performance

- Wall mounted hood
- Suitable for ducted or recirculating operation only
- 1000EE
- Maximum blower performance: 870 m³/h (freeblowing)
- Noise level from 44 dB to 75 dB
- Twin channel high performance fan motor
- Additional noise reduction insulation

Technical information

- Recirculation kit or clean air kit indicator available
- 3 speeds plus 2 intensive
- Automatic revert setting, 6 minutes
- air quality sensor
- Automatic 10 minutes after running
- Saturation display filter: grease- and charcoal filter
- 3 x LED 3W
- Light Intensity: 897 lux
- Colour Temperature: 3500 K
- Light dimmer function
- Softlight with dimmer function
- Rim ventilation
- Rim extraction
- Steel filter cover, dishwasher safe

Performance

- Energy Efficiency Class: A
- Average Energy Consumption: 33.3 kWh/year*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*

Technical Information

- Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD): 689 x 900 x 500 mm - mounting with outer chimney 809-1139 x 900 x 500 mm
 - mounting with telescopic chimney
- Chimney hood wall fixing system
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Total Connected load: 269 W
- Recirculation kit or clean air kit

* In accordance with the EU-Regulation No 65/2014

**Series 8, wall-mounted cooker hood,
90 cm, Stainless steel
DWB091K50**

