

Series 2, wall-mounted cooker hood, 60 cm, clear glass, Stainless Steel DWG068D50I



DHZ5467	Recirculating kit
DHZ5477	Active carbon filter
DHZ5640	Flue Duct Extension with Bracket

**Excellent in performance – also comes
with an integrated glass to add a modern
touch to your kitchen.**

- Absorbs odors with Charcoal Replacement Filters (Available for sale)
- Ducted or Non-ducted Options
- Converts to Recirculation Mode with Accessory Kit (Separate Purchase Required)

Color chimney: Stainless steel
 Typology: Wall-mounted
 Height of product, without chimney: 330 mm
 Net weight: 13.6 kg
 Type of control: mechanical
 Number of speed settings: 3-stage
 Max. air recirculation: 575 m³/h
 Number of lights: 2
 Diameter of air outlet: 120 / 150 mm
 Grease filter material: Washable stainless steel
 Odour filter: No
 Operating Mode: Convertible
 Optional accessories: DHZ5467, DHZ5477, DHZ5640
 Type of lamps used: Low consumption
 Total power of the lamps: 10 W
 Clean filter reminders: No
 Voltage: 230 V
 Frequency: 50 Hz
 Plug type: India plug (6 Ampere)
 Installation typology: Wall-mounted
 Material body: Stainless steel
 Plug type: India plug (6 Ampere)
 Dimensions of the product, with chimney (if exists) (in): x x
 Dimensions of the packed product: 25.19 x 15.94 x 26.37
 Net weight: 30.000 lbs
 Gross weight: 40.000 lbs
 Motor location: Integrated motor in hood chimney
 No-return airflow flap: No
 Dimensions of the product, with chimney (if exists): 594 x 600.0 x 520.0 mm
 Dimensions of the packed product (HxWxD): 640 x 405 x 670 mm
 Net weight: 13.6 kg
 Gross weight: 18.0 kg



4 242002 972138

Series 2, wall-mounted cooker hood, 60 cm, clear glass, Stainless Steel DWG068D50I

**Excellent in performance – also comes
with an integrated glass to add a modern
touch to your kitchen.**

Design

- Straight glass and box design for wall mounting
- Brushed stainless steel and transparent glass screen
- Chromed Push buttons
- Chromed logo strip on the chimney
- Mechanical with 1x indicator LED

Key Functions

- Maximum extraction rate according to EN 61591: 705 m³/h
- Maximum blower performance: 745 m³/h (freeblowing)
- 3 fan speed settings

Comfort

- 2 x 10 W Energy-saving lighting
- Double-layered, high grade stainless steel Baffle filters
- Quiet operations at 73 dB (re 1 pW) at speed setting 3

Technical information

- For wall mounting only
- Suitable for ducted or recirculating operation only
- Dimensions of the product, with chimney (if exists)
- (HxWxD mm): 594 x 600 x 520
- Minimum clearance to gas/electric cook top: 750 mm
- Length electrical supply cord: 150 cm
- Ducting connection: 150mm/120mm diameter

* In accordance with the EU-Regulation No 65/2014

**Series 2, wall-mounted cooker hood,
60 cm, clear glass, Stainless Steel
DWG068D50I**

