

## Series 2, wall-mounted cooker hood, 90 cm, clear glass, Stainless Steel DWG098D50I



DHZ5640 Flue Duct Extension with Bracket  
 DHZ5467 Recirculating kit  
 DHZ5477 Active carbon filter

**Excellent in performance – also comes  
with an integrated glass to add a modern  
touch to your kitchen.**

- Converts to Recirculation Mode with Accessory Kit (Separate Purchase Required)
- Absorbs odors with Charcoal Replacement Filters (Available for sale)
- Ducted or Non-ducted Options

Color chimney: ..... Stainless steel  
 Typology: ..... Wall-mounted  
 Height of product, without chimney: ..... 330 mm  
 Net weight: ..... 15.6 kg  
 Type of control: ..... mechanical  
 Number of speed settings: ..... 3-stage  
 Max. air recirculation: ..... 575 m<sup>3</sup>/h  
 Number of lights: ..... 2  
 Diameter of air outlet: ..... 120 / 150 mm  
 Grease filter material: ..... Washable stainless steel  
 Odour filter: ..... No  
 Operating Mode: ..... Convertible  
 Optional accessories: ..... DHZ5640, DHZ5467, DHZ5477  
 Type of lamps used: ..... Low consumption  
 Total power of the lamps: ..... 10 W  
 Clean filter reminders: ..... No  
 Voltage: ..... 230 V  
 Frequency: ..... 50 Hz  
 Plug type: ..... India plug (6 Ampere)  
 Installation typology: ..... Wall-mounted  
 Material body: ..... Stainless steel  
 Plug type: ..... India plug (6 Ampere)  
 Dimensions of the product, with chimney (if exists) (in): ..... x x  
 Dimensions of the packed product: ..... 24.80 x 15.94 x 38.18  
 Net weight: ..... 34.000 lbs  
 Gross weight: ..... 50.000 lbs  
 Motor location: ..... Integrated motor in hood chimney  
 No-return airflow flap: ..... No  
 Dimensions of the product, with chimney (if exists): ..... 594 x 900.0 x 520.0 mm  
 Dimensions of the packed product (HxWxD): ..... 630 x 405 x 970 mm  
 Net weight: ..... 15.6 kg  
 Gross weight: ..... 22.5 kg



**Series 2, wall-mounted cooker hood,  
90 cm, clear glass, Stainless Steel  
DWG098D50I**

**Excellent in performance – also comes  
with an integrated glass to add a modern  
touch to your kitchen.**

---

**Design**

- Straight glass and box design for wall mounting
- Brushed stainless steel and transparent glass screen
- Chromed Push buttons
- Chromed logo strip on the chimney
- Mechanical with 1x indicator LED

**Key Functions**

- Maximum extraction rate according to EN 61591: 705 m<sup>3</sup>/h
- Maximum blower performance: 745 m<sup>3</sup>/h (freeblowing)
- 3 fan speed settings

**Comfort**

- 2 x 10 W Energy-saving lighting
- Double-layered, high grade stainless steel Baffle filters
- Quiet operations at 73 dB (re 1 pW) at speed setting 3

**Technical information**

- For wall mounting only
- Suitable for ducted or recirculating operation only
- Dimensions of the product, with chimney (if exists)
- (HxWxD mm): 594 x 900 x 520
- Minimum clearance to gas/electric cook top: 750 mm
- Length electrical supply cord: 150 cm
- Ducting connection: 150mm/120mm diameter

\* In accordance with the EU-Regulation No 65/2014

**Series 2, wall-mounted cooker hood,  
90 cm, clear glass, Stainless Steel  
DWG098D50I**

