

**Series 6, Freestanding dual fuel
cooker, Stainless steel
HXR390I50K**



**The freestanding cooker with gas cooktop
and gas oven: achieve good results on one
level.**

- **LED display control, red:** easy-to-use thanks to the time functions.
- **High-quality materials and workmanship – continuous cast-iron pan supports.**
- **Cleaning Assistance: less cleaning effort thanks to the new cleaning option, which can be especially used for cleaning of light soiling.**

Built-in / Free-standing:	Freestanding
Dimensions:	850-865x600x600 mm
Length electrical supply cord:	100.0 cm
Net weight:	54.4 kg
Gross weight:	59.2 kg
Integrated Cleaning system:	Hydrolytic
Broil Element Wattages cavity 1:	2800 W
Power of heating element (kW):	3.5 kW
Power of 3rd heating element (kW):	1.75 kW
Energy efficiency rating:	A
Energy consumption per cycle conventional (2010/30/EC):	0.98 kWh/cycle
Energy consumption per cycle forced air convection (2010/30/EC):	0.79 kWh/cycle
Energy efficiency index (2010/30/EC):	95.2 %
Connection rating:	3300 W
Fuse protection:	16 A
Voltage:	220-240 V
Frequency:	50 Hz
Plug type:	India plug (16 Ampere)
Energy input:	Mixed electro/gas
Gas type:	Liquidgas G30,31 28-30/37 mbar
Gross weight:	131.000 lbs
Length electrical supply cord:	100.0 cm
Dimensions:	850-865x600x600 mm
Dimensions of the packed product (HxWxD): ...	1015 x 655 x 680 mm



Series 6, Freestanding dual fuel cooker, Stainless steel HXR390I50K

The freestanding cooker with gas cooktop and gas oven: achieve good results on one level.

- Built-in Gas combination freestanding cooker, stainless steel
- HXR390I50K stainless steel

Cooktop

- Burners: 2 standard, 1 economy, 1 wok burner
- Front left: wok burner 3.5 KW
- Rear left: standard burner 1.75 KW
- Rear right: standard burner 1.75 KW
- Front right: economy burner 1 KW
- One-hand ignition via control knobs
- Flame failure safety device
- cast iron pan supports dishwasher proof
- glass cover lid

Heating Functions

- Gas combination freestanding cooker with 9 heating methods:
- Hot Air
- Conventional heat Hot air grilling Pizza setting Bottom heat Defrost pre-heating
- Cavity volume: 66 l

Hook-in racks / rails

- Removable wire shelf support rails

Design

Colour display: red

Comfort

- LED display control (red)
- Electronic clock
- Rapid heating-up
- Rapid heating-up: manual
- Standard drawer for kitchen utensils

Accessories

Connecting cable: 100 cm

- Child lock
- Energy efficiency rating (acc. EU Nr. 65/2014): A (at a range of energy efficiency classes from A+++ to D)
- Energy consumption per cycle in conventional mode: 0.98 kWh
- Energy consumption per cycle in fan-forced convection mode: 0.79 kWh
- Number of cavities: 1 Heat source: electrical Cavity volume: 66 l
- Energy efficiency rating (acc. EU Nr. 65/2014): A (at a range of energy efficiency classes from A+++ to D)
- Energy consumption per cycle in conventional mode: 0.98 kWh
- Energy consumption per cycle in fan-forced convection mode: 0.79 kWh
- Number of cavities: 1 Heat source: electrical Cavity volume: 66 l

Technical Information

- Length of mains cable: 100 cm
- Nominal voltage: 220 - 240 V
- Total connected load electric: 3.3 KW
- Total connected load gas: 8 KW
- Preset for liquid gas, (28 - 30/37 mbar)
- NG H/E 20mbar, E+ 20/25mbar

Dimensions:

- Appliance dimension (h x w x d): 850 mm x 600 mm x 600 mm
- Adjustable feet