

**Serie | 6, island cooker hood, 90 cm,
Stainless steel
DIB98JQ50**

A+



The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- **PerfectAir sensor:** automatic control of settings for maximal extractor performance with minimal noise.
- **Extra silent:** the high-performance hood, with minimal noise.
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **Grease filtration level:** filters out over 85% of the grease from kitchen air
- **EcoSilence Drive:** our highly efficient motor saves on energy, not on performance.

Technical Data

Typology : Island/Ceiling
 Approval certificates : CE, Eurasian, VDE
 Length electrical supply cord : 130 cm
 Height of the chimney : 698-878/698-998 mm
 Height of product, without chimney : 46 mm
 Net weight : 32.714 kg
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction : 445 m³/h
 Boost position output recirculating : 457 m³/h
 Maximum output recirculating air : 353 m³/h
 Boost position air extraction : 867 m³/h
 Number of lights : 4
 Noise level : 54 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable stainless steel
 Odour filter : No
 Operating Mode : Convertible
 Delay Shut off modes : 10 min
 Optional accessories : DHZ1231, DHZ1241, DHZ1246, DHZ1251, DHZ1253, DHZ1256, DHZ5346, DHZ5385, DIZ2CB114, DZZ1XX1B6, DIZ2CX5C6, DIZ2FX5D1, DZZ0XX0P0, DZZ2CB1B4
 Type of lamps used : LED
 Grease filter type : Kasette
 Connection Rating : 166 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : Gardy plug w/ earthing
 Installation typology : Island
 Material body : Stainless steel
 Approval certificates : CE, Eurasian, VDE
 Plug type : Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product : 33.07 x 24.01 x 40.94
 Net weight : 72.000 lbs
 Gross weight : 91.000 lbs
 Motor location : Integrated motor in hood chimney
 No-return airflow flap : Yes
 Length electrical supply cord : 130 cm
 Dimensions of the product, with chimney (if exists) : 744-1044 x 898.0 x 600.0 mm
 Dimensions of the packed product (HxWxD) : 840 x 610 x 1040 mm
 Net weight : 32.714 kg
 Gross weight : 41.5 kg



Serie | 6, island cooker hood, 90 cm, Stainless steel DIB98JQ50

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 31.6 kWh/year
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 44/54 dB

Variant:

Design:

Technical information

Performance

Power:

Environment and safety:

Comfort:

Measures:

Technical information

- Island Hood Brushed steel
- 90 cm wide
- 90 cm Island chimney hood, Brushed steel
- Suitable for ducted or re-circulated extraction
- For recirculated extraction standard recirculation kit or Clean Air Plus recirculation kit (accessory) needed
- Ceiling mounted hood
- TouchControl
- Electronic controls
- TouchControl with lightline
- 3 speeds plus 2 intensive via TouchControl
- Electronic controls via TouchControl with lightline
- TouchControl (3 speeds plus 2 intensive) with lightline
- 3 speeds plus 2 intensive
- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- easy to clean Innerframe
- Air quality sensor
- Light dimmer function
- SoftLight
- Efficient BLDC-technology
- 4 x 1,5 W LED
- Light Intensity: 423 lux
- Colour Temperature: 3500 K
- Saturation indicator for grease filter and odor filter
- Stainless steel filter covers, dishwasher safe
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 445 m³/h
Intensive 867 m³/h
- Extraction rate exhaust air according to EN 61591 max. 867 m³/h
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 445 m³/h
Intensive 867 m³/h
- Extraction rate exhaust air according to EN 61591:
max. normal use 445 m³/h, intensive 867 m³/h
- Dimensions recirculating with CleanAir Plus recirculation kit (HxWxD): 812-1044 x 898 x 600 mm
- Additional noise insulation
- Noise level according to EN 60704-2-13 at max. normal use exhaust air: Noise, max. speed in normal us: 54 dB dB(A) re 1 pW
- Noise level according to EN 60704-2-13 exhaust air:
Max. normal use: 54 dB(A) re 1 pW
Intensive: 69 dB(A) re 1 pW
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 867 m³/h
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Power rating: 166 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V

** In accordance with the EU-Regulation No 65/2014*

**Serie | 6, island cooker hood, 90 cm,
Stainless steel
DIB98JQ50**

