

Series 8, Flex induction hob, 80 cm, surface mount with frame PXV875DC1E













HEZ32WA00 Wireless food thermometer, HEZ390012 Steaming Rack for Stainless Steel roaste, HEZ390090 Wok Set consisting of 3 Items, HEZ390210 System pan diameter 15 cm, HEZ390220 System pan diameter 19 cm, HEZ390230 System pan diameter 21cm, HEZ390512 Teppan Yaki (large), HEZ390522 Griddle Plate, HEZ394301 Connecting strip, HEZ9CF240 Fry pan, coated 24cm Ø, HEZ9CF280 Fry pan, coated 28cm Ø, HEZ9ES100 Espresso maker 4 cups, HEZ9FE280 Iron pan Ø 18 / 28 cm, HEZ9FF010 Flex Pan, large, HEZ9FF030 Flex Pan set, 3 pcs., HEZ9FF040 Flex Pan set, 4 pcs., HEZ9SE040 4 pieces Set, HEZ9SE060 6 pieces Set, HEZ9TY010 Teppan Yaki, HZ390011 Stainless Steel roaster with glas lid


- **DirectSelect Premium**: direct, simple selection of the desired cooking zone, power and additional functions.
- FlexInduction: more flexibility on your hob for large pots and pans.
- PerfectFry: no more worries about scorching.
- Comfort Profile: elegant, appealing design with bevelled front and metal strips on the side.
- Move Mode: divides the cooking zone in three power levels for boiling, cooking and simmering.


Product name/family: Cooking zone ceramic
Built-in / Free-standing:
Energy input:Electric
Total number of positions that can be used at the same time: 5
Required niche size for installation (HxWxD): 51 x 750-780 x 490-500
mm
Width of the appliance:816 mm
Dimensions: 51x816x527 mm
Dimensions of the packed product (HxWxD): 126 x 953 x 603 mm
Net weight:15.6 kg
Gross weight:
Residual heat indicator:yes
Location of control panel:Front
Basic surface material:
Color of surface:
Length electrical supply cord:
Sealed Burners:
Power Boost:
Power of heating element (kW):
Power of 3rd heating element (kW):
Power of heating element (kW in boost):
Power of 3rd heating element (kW in boost):
Connection rating:
Voltage: 220-240 V
Frequency:
Energy input:
• .
Plug type:
Appliance Dimensions (h x w x d) (in):
Dimensions of the packed product: 4.96 x 23.74 x 37.51
Net weight: 34.000 lbs
Gross weight:
Total number of positions that can be used at the same time: 5
Length electrical supply cord:
Required niche size for installation (HxWxD): 51 x 750-780 x 490-500
mm
Dimensions:
Dimensions of the packed product (HxWxD): 126 x 953 x 603 mm
Net weight:
Gross weight:





Series 8, Flex induction hob, 80 cm, surface mount with frame PXV875DC1E





- A: Minimum distance from the hob cut-out to the wall.
 B: Recessed depth
 C: The clearance between the surface of the worktop and the top of the front of the oven must be 30 mm. See space requirements for the oven.

The worktop into which the hob is installed must withstand loads of approx. 60 kg; suitable substructures must be used if required.

D	E	F
585-600	50	≥ 35
> 600	> 50	> 50

① Ventilation gap must be present

All measurements in mm

