

**Serie | 6, Island cooker hood, 90 cm,
Stainless steel
DIB98JQ50B**

A+



The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- **EcoSilence Drive:** our highly efficient motor saves on energy, not on performance.
- **PerfectAir sensor:** automatic control of settings for maximal extractor performance with minimal noise.
- **DirectSelect control:** direct selection of desired settings and light.
- **extra silent:** maximal extractor performance with very minimal noise.
- **Grease filtration level:** filters out up to 89.2% of the grease from kitchen air.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	698-878/698-998
Height of product, without chimney (mm) :	46
Net weight (kg) :	30.424
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	445
Boost position output recirculating (m ³ /h) :	391
Maximum output recirculating air (m ³ /h) :	313
Boost position air extraction (m ³ /h) :	867
Number of lights :	4
Noise level (dB(A) re 1 pW) :	54
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
Odour filter :	No
Operating Mode :	Convertible
Delay Shut off modes :	10M
Optional accessories :	DHZ1231, DHZ1241, DHZ1246, DHZ1251, DHZ1253, DHZ1256, DHZ5346, DHZ5385, DIZ2CX5C6, DIZ2FX5D1, DSZ5201, DSZ6230, DZZ0XX0P0, DZZ1XX1B6
Type of lamps used :	LED
Grease filter type :	Kassette
Connection Rating (W) :	166
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation typology :	Island
Material body :	Stainless steel
Approval certificates :	CE, VDE
Plug type :	GB plug
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	33.07 x 24.01 x 40.94
Net weight (lbs) :	67
Gross weight (lbs) :	86
Motor location :	Integrated motor in hood chimney
No-return airflow flap :	No
Length electrical supply cord (cm) :	130
Dimensions of the product, with chimney (if exists) (mm) :	744-1044 x 898 x 600
Dimensions of the packed product (HxWxD) (mm) :	840 x 610 x 1040
Net weight (kg) :	30.424
Gross weight (kg) :	39.2



Serie | 6, Island cooker hood, 90 cm, Stainless steel DIB98JQ50B

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

Technical information

- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Connected load: 166 W
- Electrical cable length 1.3 m

** In accordance with the EU-Regulation No 65/2014*

Design

- Island chimney hood, 90 cm
- 90 cm wide
- Appliance colour: Brushed steel
- Ceiling mounted hood
- Electronic controls via TouchControl

Operating mode / operation

- 3-stage + 2 intensive
- Max. extraction rate: 867 m³/h
- Extraction rate according to DIN/EN 61591 ø 15 cm: max.
Normal 445 m³/h Intensive 867 m³/h
- Extraction rate in recirculation mode:
Max. normal use: 313 m³/h
Intensive: 391 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13
exhaust air at normal use max.: 54 dB(A) re 1 pW (54 dB(A) re
20 µPa sound pressure)
- Noise levels in recirculation mode:
Max. normal use: 71 dB(A) re 1 pW (58 dB(A) re 20 µPa sound
pressure)
Intensive: 74 dB(A) re 1 pW (61 dB(A) re 20 µPa sound
pressure)
- Energy Efficiency Class: A+ (at a range of energy efficiency
classes from A++ to E)
- Average Energy Consumption: 31.6 kWh/year*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Noise min./max. Normal Level: 44/54 dB*

Comfort

- Suitable for ducted or re-circulated extraction
- air quality sensor 1.1
- Cass.w.stainl. st. perf. plate
- Metal grease filter, dishwasher safe
- easy to clean yes
- Light dimmer function
- SoftLight
- 4 x 1,5W LED
- Light Intensity: 423 lux
- Colour Temperature: 3500 K

**Serie | 6, Island cooker hood, 90 cm,
Stainless steel
DIB98JQ50B**

