

**Serie | 4, Wall-mounted cooker hood,
90 cm, Stainless steel
DWB97DM50A**

B



Box-design hood: performance and matching kitchen design bundled in one hood.

- **TouchSelect control:** quick touch-control selection of desired settings and light.
- **Extraction rate:** at 740 m³/h, it quickly ensures optimal kitchen air quality.
- **Silent:** maximal extractor performance with little noise
- **LED lighting:** for perfect, energy-efficient illumination of the cooktop.
- **Intensive speed setting with reset:** automatically resets the hood to normal speed setting after 6 min..

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	Australia Standards, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	583-912/583-1022
Height of product, without chimney (mm) :	53
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	13.327
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	454
Boost position output recirculating (m ³ /h) :	379
Maximum output recirculating air (m ³ /h) :	324
Boost position air extraction (m ³ /h) :	739
Number of lights :	2
Noise level (dB) :	65
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242005087594
Connection Rating (W) :	255
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	60; 50
Plug type :	AU plug
Installation typology :	Wall-mounted



4 242005 087594

Serie | 4, Wall-mounted cooker hood, 90 cm, Stainless steel DWB97DM50A

**Box-design hood: performance and matching
kitchen design bundled in one hood.**

Design

- Wall mounted design
-
- Sliding controls for power settings and lights
- 3 power settings plus intensive setting

Operating and power

- Max. extraction rate: 740 m³/h
- Noise min./max. Normal Level: 52/65 dB*
- 2 x 1,5W LED
- Supplied with 3 dishwasher safe metal grease filters Metal grease filter

Technical Information

- Suitable for ducted or recirculating operation
- Electronic saturation display for metal grease and active carbon filter
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Appliance (ducted air): 635-965 MM x 900 x 500 mm
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
703 x 900 x 500 mm - mounting with outer chimney
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Dimensions recirculating with cleanAir module (HxWxD);
703 x 900 x 500 mm - mounting with outer chimney
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Dimensions recirculating with CleanAir module (HxWxD):
703 x 900 x 500 mm - mounting with outer chimney
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- 255 W total connected load
- Electrical cable length 1.3 m

**Serie | 4, Wall-mounted cooker hood, 90 cm,
Stainless steel
DWB97DM50A**

