

**Serie | 6, Wall-mounted cooker hood,
90 cm, Stainless steel
DWW098E50A**

A⁺



The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- **Extraction rate:** at 860 m³/h, it quickly ensures optimal kitchen air quality.
- **Especially quiet:** high performance at just 41 dB.
- **Intensive speed setting with reset:** automatically resets the hood to normal speed setting after 6 min..

Technical Data

Typology :	Chimney
Approval certificates :	Australia Standards, CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-864/582-974
Height of product, without chimney (mm) :	90
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	18.618
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	460
Boost position output recirculating (m ³ /h) :	460.0
Boost position air extraction (m ³ /h) :	860
Number of lights :	3
Noise level (dB) :	55
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242002813486
Connection Rating (W) :	169
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	AU plug
Installation typology :	Wall-mounted



4 242002 813486

Serie | 6, Wall-mounted cooker hood, 90 cm, Stainless steel DWW098E50A

**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom in
your kitchen planning.**

Design:

- Stainless steel
- Canopy Rangehood
- Slimline design
- Wall mounted hood
- Ducted and recirculated air operation

Comfort:

- Electronic controls via Push button controls with digital display
- Automatic 10 minute run-on function
- Electronic saturation display for metal grease and active carbon filter
- Wall fixing system
- Intensive setting with automatic switch back to previous setting
- Saturation indicator for metal & carbon filters
- Special chimney solutions possible
- Dual filter system with outer aluminium frame and inner metal grease filter
- Supplied with 3 dishwasher safe metal grease filters Metal grease filter
- Additional noise insulation

Operating and power:

- 169 W total connected load
- 46 dB at 300 m³/h (150 mm ducted)
- Light Intensity: 897 lux

Dimensions (HxWxD):

- Appliance (ducted air): 672-954 x 900 x 500 mm

Technical Information:

- 220 - 240 V/60 Hz
- Extraction rate exhaust air according to EN 61591:
max. normal use 460 m³/h, intensive 860 m³/h

**Serie | 6, Wall-mounted cooker hood, 90 cm,
Stainless steel
DWW098E50A**

