

Series 6, Gas cooktop, 90 cm, Tempered glass, Black PPS9A6B91A





HEZ298105 Simmer plate

The tempered-glass gas cooktop with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

- FlameSelect: adjust the gas flame precisely using nine defined levels.
- Wok burner: powerful cooking at up to 4 kW (depending on gas type).
- Semi-continuous cast-iron pan support: for high stability and easy cleaning.
- Sword knobs: for an ergonomic control.
- Surface colour: elegant black tempered-glass design.

Product name/family:gas hob w integrated controls Built-in / Free-standing:Built-in
Energy type:Gas
Total number of positions that can be used at the same time: 5
Type of control setting devices:
Required niche size for installation (HxWxD): 45 x 850-852 x 490-502
mm
Width of the appliance:915 mm
Dimensions:
Dimensions of the packed product (HxWxD): 165x1116x659 mm
Net weight:
Gross weight:
Residual heat indicator: without
Location of control panel: Front
Basic surface material:Tempered glass
Color of surface:Black
Color of frame:
Length electrical supply cord:
EAN code:
Gas connection rating:
Fuse protection:3 A
Voltage:
Frequency: 50; 60 Hz





Series 6, Gas cooktop, 90 cm, Tempered glass, Black PPS9A6B91A

The tempered-glass gas cooktop with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

Design

- Black Tempered Glass surface
- Individual cast iron pan supports

Comfort & Convenience

- FlameSelect (9 steps): precisely adjust the flame in nine defined and consistent levels.
- Sword control knobs: controls with comfortable grip for easy turning.
- One-hand electronic ignition via controls: just push and turn the control knob to ignite the flame.

Burners and power

- 5 Gas burners
- Left: Wok burner up to 15 Mj/h (depending on gas type)
- Center front: Economy burner up to 4 Mj/h (depending on gas type)
- Center rear: Standard burner up to 6.85 Mj/h (depending on gas type)
- Right rear: High-speed burner up to 11 Mj/h (depending on gas type)
- Right front: Standard burner up to 6.85 Mj/h (depending on gas type)

Safety

- Flame failure device fitted to each individual burner: prevents unwanted gas flow when flame goes out.

Installation

- Dimensions of the product (HxWxD mm): 58 x 915 x 520
- Required niche size for installation (HxWxD mm) : $45 \times 850 \times (490 502)$
- Min. worktop thickness: 30 mm

Accessories

- 1 x Wok attachment ring, cross support for espresso included