





The DownDraft hood provides an open view into the kitchen and clear views from the hob thanks to a high extraction rate. When not in use it simply dissapears into the worktop.

- LED lighting: For optimal, energy-efficient illumination of your hob
- Intensive speed setting: Removes strong kitchen odours quickly and effectively
- Flexible installation of the motor allows for maximum space inside the cabinet.
- Extraction rate: A remarkable power of 380m3/h which ensures optimal kitchen air quality.
- Especially quiet: High performance at just 62 dB

Technical Data

Typology: Downdraft

Length electrical supply cord: 150 cm

Min. required niche size for installation (HxWxD): 738mm x

844.0mm x 104mm mm Net weight : 35.3 kg Type of control : Electronic

Number of speed settings: 3-stage + 2 intensive Maximum output air extraction: 530 m³/h Boost position output recirculating: 500.0 m³/h Maximum output recirculating air: 452 m³/h Boost position air extraction: 750 m³/h

Number of lights: 1

Noise level : 62 dB(A) re 1 pW Diameter of air outlet : 150 mm

Grease filter material: Washable aluminium

Odour filter : No

Operating Mode : Convertible Delay Shut off modes : 10 min

Optional accessories: DSZ9ID0M0, DSZ9ID0P0, DSZ9ID0Q0

Grease filter type : Kassette Connection Rating : 317 W Fuse protection : 10 A Voltage : 220-240 V Frequency : 50 Hz Plug type : GB plug

Installation typology : Built-in Material body : Glass, Stainless steel

Plug type : GB plug

Dimensions of the product, with chimney (if exists) (in) : / x x Dimensions of the packed product : 17.04 x 38.11 x 39.56

Net weight: 78.000 lbs Gross weight: 113.000 lbs

Motor location: Integrated motor in hood body

No-return airflow flap: No

Length electrical supply cord: 150 cm

Dimensions of the product, with chimney (if exists) : x 918.0 $\ensuremath{\text{x}}$

268.0 mm

Dimensions of the packed product (HxWxD): 433 x 968 x 1005

mm

Net weight : 35.3 kg Gross weight : 51.1 kg





The DownDraft hood provides an open view into the kitchen and clear views from the hob thanks to a high extraction rate. When not in use it simply dissapears into the worktop.

Performance

- 3 fan speeds setting plus 2 intensive
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use530m³/h Intensive750 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:

Max. normal use:62 dB(A) re 1 pW (48dB(A) re 20 μ Pa sound pressure) Intensive:67 dB(A) re 1 pW (53 dB(A) re 20 μ Pa sound pressure)

- Extraction rate in recirculation mode: Max. normal use:452m³/h Intensive:500 m³/h
- Noise levels in recirculation mode: Max. normal use:72 dB(A) re 1 pW (58dB(A) re 20 μPa sound pressure) Intensive:75 dB(A) re 1 pW (61 dB(A) re 20 μPa sound pressure)

Design

- TouchControl for extractor speeds and light

Key Functions


- Automatic intensive revert after 5/10 min
- Automatic run on for 10 min.
- Rim ventilation
- Removable metal grease filter, dishwasher safe
- Saturation indicator for metal and charcoal filter
- Energy Efficiency Class: A

Technical information:

- Suitable for regular or flush installation in worktops.
- Suitable for ducted or recirculating operation
- In recirculation mode no combination with gas hobs allowed.
- Extension height 300 mm
- Recirculating kit
- Electrical connection rating: 317 W
- Dimensions recirculating (HxWxD): 738 1038 x 918 x 268 mm
- Dimensions exhaust air (HxWxD): 738 1038 x 918 x 268 mm
- * In accordance with the EU-Regulation No 65/2014





Combination with electric hob




For use with gas hob see drawing "Combination with gas hob".

measurements in mm









For flush installation in stone and granite work surfaces

measurements in mm





The motor unit can be fitted at a maximum distance of three metres from the appliance. (Special accessory required)



Combination with gas hob 75 cm



Use with gas hob only possible in air extraction mode.
Total maximum output: 11.9 kW
Maximum output of wok 4.2 kW.
Total maximum output of rear hobs: 4.7 kW


measurements in mm

Combination with gas hob 90 cm



Use with gas hob only possible in air extraction mode.
Total maximum output: 13.7 kW
Maximum output of wok 6 kW.
Total maximum output of rear hobs: 4.7 kW

measurements in mm



Only install one side of the appliance at least 50 mm from a high-sided unit or a wall.

- * 650 mm depth only in combination with
- slim hobs. **min. 750 mm for hobs with 500 mm cut-out depth. measurements in mm