

## Series 8, Telescopic cooker hood, 90 cm, Stainless steel DFS098K53



DSZ4920	Installation kit for 90cm wide wall unit
DSZ4960	Lowering frame
DWZ0IT0P0	Long Life odor filter (replacement)
DWZ1IT1D1	Long Life recirculation kit external
DSZ4561	Standard odor filter (replacement)
DSZ4565	Standard recirculation kit
DSZ4681	CleanAir active carbon filter
DSZ4683	CleanAir Recirculation Kit
DWZ1IX1B6	Clean Air Plus odor filter (replacement)
DWZ1IX1C6	Clean Air Plus recirc. kit external

## The telescopic cooker hood that disappears into your upper cabinet, giving you a sleek kitchen front.

- **LED Illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- **Intensive speed setting:** Removes strong kitchen odours quickly and effectively
- **Extra silent:** the high-performance hood, with minimal noise.

Typology: ..... Pull-out  
 Length electrical supply cord: ..... 175.0 cm  
 Min. required niche size for installation (HxWxD): 337mm x 524.0mm x 290mm mm  
 Net weight: ..... 15.0 kg  
 Type of control: ..... Electronic  
 Number of speed settings: ..... 3-stage + 2 intensive  
 Max. air extraction: ..... 412 m<sup>3</sup>/h  
 Boost position output recirculating: ..... 746 m<sup>3</sup>/h  
 Max. air recirculation: ..... 392 m<sup>3</sup>/h  
 Boost position air extraction: ..... 867 m<sup>3</sup>/h  
 Number of lights: ..... 2  
 Noise level: ..... 52 dB(A) re 1 pW  
 Diameter of air outlet: ..... 120 / 150 mm  
 Grease filter material: ..... Washable stainless steel  
 Odour filter: ..... No  
 Operating Mode: ..... Convertible  
 Optional accessories: DSZ4920, DSZ4960, DWZ0IT0P0, DWZ1IT1D1, DSZ4561, DSZ4565, DSZ4681, DSZ4683, DWZ1IX1B6, DWZ1IX1C6  
 Type of lamps used: ..... LED  
 Total power of the lamps: ..... 6 W  
 Grease filter type: ..... Kasette  
 Connection rating: ..... 166 W  
 Fuse protection: ..... 10 A  
 Voltage: ..... 220-240 V  
 Frequency: ..... 50; 60 Hz  
 Plug type: ..... Gardy plug w/ earthing  
 Installation typology: ..... Built-in  
 Material body: ..... Stainless steel  
 Plug type: ..... Gardy plug w/ earthing  
 Dimensions of the product, with chimney (if exists) (in): ..... x x  
 Dimensions of the packed product: ..... 15.74 x 37.00 x 19.29  
 Net weight: ..... 33.000 lbs  
 Gross weight: ..... 40.000 lbs  
 Motor location: ..... Integrated motor in hood body  
 No-return airflow flap: ..... No  
 Length electrical supply cord: ..... 175.0 cm  
 Dimensions of the product, with chimney (if exists): ..... 378 x 898.0 x 290.0 mm  
 Dimensions of the packed product (HxWxD): ..... 400 x 940 x 490 mm  
 Net weight: ..... 15.0 kg  
 Gross weight: ..... 17.9 kg  
 Delay Shut off modes: ..... 10 min



4 242002 966182

## **Series 8, Telescopic cooker hood, 90 cm, Stainless steel DFS098K53**

**The telescopic cooker hood that disappears into your upper cabinet, giving you a sleek kitchen front.**

---

### **Performance**

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591  $\varnothing$  15 cm:
  - max. Normal use: 411 m<sup>3</sup>/h
  - Intensive: 867 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
  - Max normal use: 52 dB
  - Intensive: 69 dB(A)

### **Design**

- Cupboard 60 or 90 cm
- For installation in a special wall cupboard
- Touch control on black full width glass panel

### **Key Functions**

- 2 x LED 3W
- 3 fan speeds setting plus 2 intensive
- Removable metal grease filter, dishwasher safe
- Saturation indicator for metal and charcoal filter
- Efficient BLDC-technology
- Automatic intensive revert after 6 min.
- air quality sensor
- Energy Efficiency Class: A

### **Technical information:**

- Dimensions of the product, with chimney (if exists) (HxWxD mm): 378 x 898 x 290
- Required niche size for installation (HxWxD mm): 337 x 524 x 290
- Length of main cable: 175 cm
- Electrical connection rating: 166 W
- Diameter pipe  $\varnothing$  150 mm ( $\varnothing$  120 mm enclosed)

**Series 8, Telescopic cooker hood, 90 cm, Stainless steel**  
**DFS098K53**

