

**Series 6, Island cooker hood, 90 cm,
Stainless steel
DIB091E51**



**The island chimney hood: Flexible ceiling
mounting for your island kitchen**

- **especially silent:** maximal extractor performance with minimal noise
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **Eco Silence Drive:** the powerful, energy-saving drive for hoods.
- **Intensive speed setting:** Removes strong kitchen odours quickly and effectively

- DHZ1231 Adapter for roof inclination left/right
- DHZ1241 Adapter for roof inclination front/back
- DHZ1246 Chimney extension 1100 mm
- DHZ1251 Extension for mounting kit 500 mm
- DHZ1253 Extension for mounting kit 1000 mm
- DHZ1256 Chimney extension 1600 mm
- DHZ5346 Standard odor filter (replacement)
- DHZ5385 Standard recirculation kit
- DSZ5201 CleanAir active carbon filter spare part
- DSZ6230 CleanAir Recirculation Kit
- DZZ0XX0P0 Long Life odor filter (replacement)

Typology:Island/Ceiling
 Length electrical supply cord: 130.0 cm
 Height of the chimney: 698-878/698-998 mm
 Height of product, without chimney:46 mm
 Net weight:28.5 kg
 Type of control:Electronic
 Number of speed settings:3-stage + 2 intensive
 Max. air extraction: 620 m³/h
 Boost position output recirculating:480.0 m³/h
 Max. air recirculation: 400 m³/h
 Boost position air extraction: 1000 m³/h
 Number of lights: 4
 Noise level:60 dB(A) re 1 pW
 Diameter of air outlet: 120 / 150 mm
 Grease filter material:Washable aluminium
 Odour filter: No
 Operating Mode:Convertible
 Optional accessories: DHZ1231, DHZ1241, DHZ1246, DHZ1251, DHZ1253, DHZ1256, DHZ5346, DHZ5385, DSZ5201, DSZ6230, DZZ0XX0P0
 Type of lamps used: LED
 Total power of the lamps:12 W
 Grease filter type:Kassette
 Connection rating: 272 W
 Fuse protection:10 A
 Voltage: 220-240 V
 Frequency: 60; 50 Hz
 Plug type: Gardy plug w/ earthing
 Installation typology: Island
 Material body: Stainless steel
 Plug type: Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in):x x
 Dimensions of the packed product: 32.87 x 24.01 x 40.74
 Net weight:63.000 lbs
 Gross weight: 82.000 lbs
 Motor location: Integrated motor in hood chimney
 No-return airflow flap: No
 Length electrical supply cord: 130.0 cm
 Dimensions of the product, with chimney (if exists): 744-1044 x 900.0 x 600.0 mm
 Dimensions of the packed product (HxWxD): ... 835 x 610 x 1035 mm
 Net weight:28.5 kg
 Gross weight: 37.2 kg
 Delay Shut off modes: 10 min



Series 6, Island cooker hood, 90 cm, Stainless steel DIB091E51

The island chimney hood: Flexible ceiling mounting for your island kitchen

Performance

- Suitable for ducted or recirculating operation
- Max. extraction rate according to EN 61591: 1000 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 60 dB(A) re 1 pW (46 dB(A) re 20 µPa sound pressure)
 - Intensive: 71 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)

Key Functions

- Twin channel high performance fan motor
- Push button controls with digital display
- 3 fan speeds setting plus 2 intensive
- 3 removable metal grease filter
- 4 x LED 3W
- Dimmer function

Features

- Automatic run on for 10 min.
- Automatic intensive revert after 6 min.
- Saturation indicator for metal and charcoal filter

Design

- Ceiling mounted hood
- electronic controls via Push button controls with digital display

Environment and safety:

- Removable metal grease filter, dishwasher safe

Technical information:

- Dimensions exhaust air (HxWxD mm): 744-924 x 900 x 600
- Dimensions recirculating (HxWxD mm): 744-1044 x 900 x 600
- Electrical connection rating: 272 W

**Series 6, Island cooker hood, 90 cm,
Stainless steel
DIB091E51**

