

Series 8, Island cooker hood, 120 cm, Stainless steel DIB121U50



DHZ1231	Adapter for roof inclination left/right
DHZ1241	Adapter for roof inclination front/back
DHZ1246	Chimney extension 1100 mm
DHZ1251	Extension for mounting kit 500 mm
DHZ1253	Extension for mounting kit 1000 mm
DHZ1256	Chimney extension 1600 mm
DHZ5346	Standard odor filter (replacement)
DHZ5385	Standard recirculation kit
DSZ5201	CleanAir active carbon filter spare part
DSZ6230	CleanAir Recirculation Kit
DZZ0XX0P0	Long Life odor filter (replacement)

The island chimney hood: Flexible ceiling mounting for your island kitchen

- **Especially quiet:** High performance at just 62 dB
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **Eco Silence Drive:** the powerful, energy-saving drive for hoods.
- **Intensive speed setting:** Removes strong kitchen odours quickly and effectively

Typology:	Island/Ceiling
Length electrical supply cord:	130.0 cm
Height of the chimney:	684-864/684-984 mm
Height of product, without chimney:	60 mm
Net weight:	38.3 kg
Type of control:	Electronic
Number of speed settings:	3-stage + 2 intensive
Max. air extraction:	640 m ³ /h
Boost position output recirculating:	430.0 m ³ /h
Max. air recirculation:	340 m ³ /h
Boost position air extraction:	890 m ³ /h
Number of lights:	4
Noise level:	62 dB(A) re 1 pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable stainless steel
Odour filter:	No
Operating Mode:	Convertible
Optional accessories:	DHZ1231, DHZ1241, DHZ1246, DHZ1251, DHZ1253, DHZ1256, DHZ5346, DHZ5385, DSZ5201, DSZ6230, DZZ0XX0P0
Type of lamps used:	LED
Total power of the lamps:	12 W
Grease filter type:	Multilayer
Connection rating:	272 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	60; 50 Hz
Plug type:	Gardy plug w/ earthing
Installation typology:	Island
Material body:	Stainless steel
Plug type:	Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in):	x x
Dimensions of the packed product:	34.84 x 24.01 x 52.16
Net weight:	84.000 lbs
Gross weight:	108.000 lbs
Motor location:	Integrated motor in hood chimney
No-return airflow flap:	No
Length electrical supply cord:	130.0 cm
Dimensions of the product, with chimney (if exists):	744-1044 x 1200.0 x 650.0 mm
Dimensions of the packed product (HxWxD):	... 885 x 610 x 1325 mm
Net weight:	38.3 kg
Gross weight:	49.0 kg
Delay Shut off modes:	1-9 min



Series 8, Island cooker hood, 120 cm, Stainless steel DIB121U50

The island chimney hood: Flexible ceiling mounting for your island kitchen

Performance

- Suitable for ducted or recirculating operation
- Max. extraction rate according to EN 61591: 890 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 62 dB(A) re 1 pW (48 dB(A) re 20 µPa sound pressure)
 - Intensive: 69 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)

Key Functions

- Twin channel high performance fan motor
- Push button controls with digital display
- 3 fan speeds setting plus 2 intensive
- 4 x LED 3W
- Dimmer function
- air quality sensor
- Rim ventilation

Features

- Automatic run on for 1-9 min
- Automatic intensive revert after 6 min.

Design

- 120 cm wide
- electronic controls via Push button controls with digital display

Environment and safety:

- Removable metal grease filter, dishwasher safe

Technical information:

- Dimensions exhaust air (HxWxD mm): 744-924 x 1200 x 650
- Dimensions recirculating (HxWxD mm): 744-1044 x 1200 x 650
- Electrical connection rating: 272 W

**Series 8, Island cooker hood, 120 cm, Stainless steel
DIB121U50**

