

# Series 8, Built-in oven, 60 x 60 cm, Stainless steel HBG78B950









### **Included accessories**

 $1\ x$  enamel baking tray,suit. pyrolitic clean,  $1\ x$  combination grid,  $1\ x$  universal pan, suit. pyrol. clean.,  $1\ x$  trayholder pyrolytic models

# The built-in oven with intelligent automatic programmes: the selected dish is a perfect success with minimal effort on your part.

- **3D hotair:** perfect results thanks to optimal distribution of heat on up to 3 levels simultaneously without taste transfer.
- Pop-out controls: for an easy to clean front.
- Pyrolytic self-cleaning: Automatically cleans the oven, just wipe out the ash.
- Flap door with SoftClose: the oven door closes especially gently and quietly.
- Dampened Hinges Softly and Quietly Guide the QuietClose® Door Shut.

### **Technical Data**

Gross weight: 42.8 kg

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in Integrated Cleaning system : Pyrolytic

Min. required niche size for installation (HxWxD): 590-597 x

560-568 x 550 mm

Dimensions: 595 x 595 x 548 mm

Dimensions of the packed product (HxWxD): 670 x 680 x 670

mm

Control Panel Material: Stainless steel

Door Material : Glass Net weight : 40.6 kg

Usable volume of cavity: 63 l

Cooking method: Bottom heat, Defrost setting, Full width variable grill, Half width variable grill, Hot Air, Hot Air-Eco, Hot air grilling, Intensive heat, Pizza setting, pre-heating, Soft steaming, Special baking setting, - Top and bottom heat, warming

 $Number\ of\ interior\ lights: 2$ 

Length electrical supply cord: 120.0 cm

Interior Lights - cavity 1 : 2
Pull-out system : Accessory
Clock function : Alarm, Off, On

1 x trayholder pyrolytic models

Broil Element Wattages cavity 1 : 2800 W Convection Element Wattages cavity 1 : 2100 W

Energy efficiency rating: A

Energy consumption per cycle conventional (2010/30/EC) : 0.79 kWh/cycle

Energy consumption per cycle forced air convection (2010/30/

EC): 0.70 kWh/cycle

Energy efficiency index (2010/30/EC): 86.4 %

Connection Rating: 3650 W Fuse protection: 16 A Voltage: 220-240 V Frequency: 60; 50 Hz

Plug type : Gardy plug w/ earthing Color / Material Front : Stainless steel

Energy input : Electric

Required cutout/niche size for installation (in) : x x Dimensions of the packed product :  $26.37 \times 26.37 \times 26.77$ 

Net weight: 90.000 lbs Gross weight: 94.000 lbs

Length electrical supply cord : 120.0 cm  $\,$ 

Net weight: 40.6 kg

Included accessories: 1 x enamel baking tray, suit. pyrolitic clean, 1 x combination grid, 1 x universal pan, suit. pyrol. clean., 1 x trayholder pyrolytic models





# Series 8, Built-in oven, 60 x 60 cm, Stainless steel HBG78B950

The built-in oven with intelligent automatic programmes: the selected dish is a perfect success with minimal effort on your part.

#### Performance

- 14 Heating method electr.:
- Defrost setting
- Hot Air-Eco 3D hot air plus Intensive heat Conventional heat HydroBaking Pizza setting Low temperature cooking Bottom heat Hot air grilling Full width variable grill Half width variable grill Preheating Keep warm
- Extra large 65 litre capacity

#### **Functions**

- 68 automatic programs
- Pyrolytic self-cleaning function
- Memory function

### **Features**

- Electronic control
- Clear text display
- Digital temperature display
- automatic Rapid heating-up
- Full glass inner door
- Sabbath Mode
- Heating up indicator
- Residual heat indicator
- Automatic switch off

# Design


- Control panel height 96mm: for a perfect horizontal combination with panorama appliances
- Full metal illuminated retractable controls
- Metal touch control
- Full metal bar handle
- Enamelled cavity (grey)
- Automatic temperature suggestion
- Precise temperature control 30-300° C
- Softlight
- Oven interior light to be switched-off
- 5 shelf positions


## Safety functions

- Child lock
- Child lock function: oven door can be locked
- Maximum window temperature 30° C
- Integral cooling fan




# Series 8, Built-in oven, 60 x 60 cm, Stainless steel HBG78B950





Measurements in mm



\* 20 mm for metal fascias

Measurements in mm