

Series 2, free-standing dishwasher, 45 cm, Brushed steel anti-fingerprint SPS2HKI42E

A ↑ G







SGZ1010 inlet and outlet hose extention
SGZ3003 Silver polishing cassette
SMZ1051EU Mains cable with EU-Plug 5m
SMZ5000 Dishwashing aid set
SMZ5002 Silver polishing cassette
SMZ5300 GlassSecure Tray

Connected dishwasher with noise reduction at any time via the Home Connect App.

- ExtraDry: selectable option for additional drying.
- **Height Adjustable Top Basket**: offers extra space, especially for tall dishes.
- **Home Connect**: home appliances with smart connectivity for an easier everyday life
- Favourite function: personalized function by just one touch even for downloaded programs.
- **Programme Download**: download additional programmes via the Home Connect App that fit your everyday life.

Airborne acoustical noise emissions (EU 2017/1369):46 dB(A) re 1pW Airborne acoustical noise emission class (EU 2017/1369):
Cleaning performance:
Water consumption: 8.9 l Fotal annual water consumption 220 days: 1958 l Built-in / Free-standing: Free-standing Removable top: Yes Door panel options: Not possible Height of removable worktop: 30 mm Height of the appliance: 845 mm Adjustable feet: Yes - all Maximum adjustability feet: 20 mm Adjustable plinth: No Net weight: 37.9 kg Gross weight: 39.2 kg Connection Rating: 2400 W Fuse protection: 10 A Voltage: 220-240 V Frequency: 50; 60 Hz Length electrical supply cord: 175.0 cm Plug type: Gardy plug w/ earthing Length inlet hose: 165 cm Length outlet hose: 205 cm Hidden heating element: Yes Water protection system description: Triple water protection 24h
Total annual water consumption 220 days:
Built-in / Free-standing: Free-standing Removable top: Yes Door panel options: Not possible Height of removable worktop: 30 mm Height of the appliance: 845 mm Adjustable feet: Yes - all Maximum adjustability feet: 20 mm Adjustable plinth: No Net weight: 37.9 kg Gross weight: 39.2 kg Connection Rating: 2400 W Fuse protection: 10 A Voltage: 220-240 V Frequency: 50; 60 Hz Length electrical supply cord: 175.0 cm Plug type: Gardy plug w/ earthing Length inlet hose: 165 cm Length outlet hose: 205 cm Hidden heating element: Yes Water protection system description: Triple water protection 24h
Removable top: Yes Door panel options: Not possible Height of removable worktop: 30 mm Height of the appliance: 845 mm Adjustable feet: Yes - all Maximum adjustability feet: 20 mm Adjustable plinth: No Net weight: 37.9 kg Gross weight: 39.2 kg Connection Rating: 2400 W Fuse protection: 10 A Voltage: 220-240 V Frequency: 50; 60 Hz Length electrical supply cord: 175.0 cm Plug type: Gardy plug w/ earthing Length inlet hose: 165 cm Length outlet hose: 205 cm Hidden heating element: Yes Water protection system description: Triple water protection 24h
Door panel options:
Height of removable worktop:
Height of the appliance:
Adjustable feet: Yes - all Maximum adjustability feet: 20 mm Adjustable plinth: No Net weight: 37.9 kg Gross weight: 2400 W Fuse protection: 10 A Voltage: 220-240 V Frequency: 50; 60 Hz Length electrical supply cord: 175.0 cm Plug type: Gardy plug w/ earthing Length inlet hose: 165 cm Length outlet hose: 205 cm Hidden heating element: Yes Water protection system description: Triple water protection 24h
Maximum adjustability feet:
Adjustable plinth: No Net weight: 37.9 kg Gross weight: 39.2 kg Connection Rating: 2400 W Fuse protection: 10 A /oltage: 220-240 V Frequency: 50; 60 Hz Length electrical supply cord: 175.0 cm Plug type: Gardy plug w/ earthing Length inlet hose: 165 cm Length outlet hose: 205 cm Hidden heating element: Yes Water protection system description: Triple water protection 24h
Net weight:
Gross weight: 39.2 kg Connection Rating: 2400 W Fuse protection: 10 A /oltage: 220-240 V Frequency: 50; 60 Hz Length electrical supply cord: 175.0 cm Plug type: Gardy plug w/ earthing Length inlet hose: 165 cm Length outlet hose: 205 cm Hidden heating element: Yes Water protection system description: Triple water protection 24h
Connection Rating: 2400 W Fuse protection: 10 A /oltage: 220-240 V Frequency: 50; 60 Hz Length electrical supply cord: 175.0 cm Plug type: Gardy plug w/ earthing Length inlet hose: 165 cm Length outlet hose: 205 cm Hidden heating element: Yes Water protection system description: Triple water protection 24h
Fuse protection:
/oltage:
Frequency:
Length electrical supply cord:
Plug type:
Length inlet hose:
Length outlet hose:
Hidden heating element: Yes Water protection system description: Triple water protection 24h
Nater protection system description: Triple water protection 24h
· · · · · · · · · · · · · · · · · · ·
omica carrety activities in minimum bacteri casponers.
Nater softener:Yes
Top basket type: Practical loading with Vario Flex basket
Adjustable upper basket: Single
Bottom basket type:R2 45 cm
Brd Rack:
Optional accessories:SGZ1010, SGZ3003, SMZ1051EU, SMZ5000,
SMZ5002, SMZ5300
ncluded accessories : no
Number of place settings:10
Color / Material panel: Stainless steel colour, lacqu.
Color / Material body:Brushed steel anti-fingerprint
Color / Material top:Stainless steel colour, lacqu.
Dimensions of the product (HxWxD):845 x 450 x 600 mm
Dimensions of the packed product (HxWxD): 880 x 510 x 670 mm







Series 2, free-standing dishwasher, 45 cm, Brushed steel anti-fingerprint SPS2HKI42E

Connected dishwasher with noise reduction at any time via the Home Connect App.

Features

General Specification

Safety

- Heat exchanger
- AquaSensor
- DosageAssist
- EcoSilence Drive
- Detergent Automation
- Self-cleaning filter system with 3-fold corrugated filter

Baskets and Racks

- Height adjustable top basket
- 2 foldable plate racks in bottom basket
- Cutlery rack in top basket

Comfort

- Panel legend: Plain text (english)
- Remaining programme time indicator (min)
- Electronic delay timer: 1-24 hours
- AntiFingerprint surface coating

Programmes

- AquaStop with guarantee
- Childproof control lock
- Glass care system

Performance

Innovation and Technology

- Product dimensions (HxWxD): 84.5 x 45 x 60 cm

Series 2, free-standing dishwasher, 45 cm, Brushed steel anti-fingerprint SPS2HKI42E

