

Electric Cooktop, Black, surface mount with frame NET5054UC



- PreciseSelect® Direct Cooking Level Selection (17 Settings)
- Sleek Touch Control Panel Offers a Choice of 17 Settings for Unprecedented Temperature Control.
- Bridge Element Accomodates Oblong or Oversized Pans and Griddles
- Dual Elements Offer the Capability to use Multiple Pan Sizes
- High-end Stainless Steel Frame for a Premium Look

UPC code:	825225867623
Color:	Black
Energy source:	Electric
Fuse protection:	32 A
Volts:	240/208 V
Frequency:	60 Hz
Plug type:	no plug
Required Cutout Size (HxWxD) (in):	4" x 28 7/8" x 20"
Minimum distance from counter front (in):	2 1/4"
Minimum distance from rear wall (in):	2"
Overall appliance dimensions (HxWxD) (in):	1/4"+4" x 31" x 21 1/4"
Product Packaging Dimensions (HxWxD):	7 7/8" x 37 3/8" x 24"
Net Weight:	27.000 lbs
Gross weight:	35.000 lbs
Total number of cooktop burners:	4





Electric Cooktop, Black, surface mount with frame NET5054UC

Key Features

- PreciseSelect® Direct Cooking Level Selection (17 Settings)
- Sleek Touch Control Panel Offers a Choice of 17 Settings for Unprecedented Temperature Control.
- Bridge Element Accomodates Oblong or Oversized Pans and Griddles
- Dual Elements Offer the Capability to use Multiple Pan Sizes

Design

- High-end Stainless Steel Frame for a Premium Look


Performance

Convenience


- CleanLock Prevents Unwanted Changing of Setting While Cleaning Spills
- Keep Warm function allows meals to remain ready to serve $% \left(1\right) =\left(1\right) \left(1\right)$
- Two-Level Heat Indicator Warns if Cooktop is Warm or Hot
- ChildLock Prevents the Cooktop from Being Accidentally Switched On, Locks Temperature Settings if in Use



Electric Cooktop, Black, surface mount with frame NET5054UC



measurement in inches (mm)



mum distance between the cooktop surface and er edge of the exhaust hood. Dimensions in inches (mm)