

**Series 4, Wall-mounted cooker hood, 90 cm, Stainless steel
DWB97IM50**



Box-design hood: performance and matching kitchen design bundled in one hood.

- **Silence:** maximal extractor performance with little noise
- Enjoy the benefits of a cleaner and healthier kitchen, free from excessive grease and unwanted odors.
- **TouchSelect control:** Quickly select hood settings via touch.
- **LED-Illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- **Intensive speed setting:** removes strong kitchen odours especially quickly and effectively.

Technical Data

Color chimney : Stainless steel
 Typology : Wall-mounted
 Length electrical supply cord : 130 cm
 Height of the chimney : 583-912/583-1022 mm
 Height of product, without chimney : 53 mm
 Net weight : 13.9 kg
 Type of control : Electronic
 Number of speed settings : 3-stages + intensive setting
 Maximum output air extraction : 454 m³/h
 Boost position output recirculating : 499 m³/h
 Maximum output recirculating air : 404 m³/h
 Boost position air extraction : 739 m³/h
 Number of lights : 2
 Noise level : 65 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable stainless steel
 Odour filter : No
 Operating Mode : Convertible
 Optional accessories : DHZ1225, DHZ1235, DHZ9550, DHZ9551, DWZ0XX0J0, DWZ1DX1B4, DWZ1DX1I4, DWZ1DX1I6, DWZ1FX5C6, DWZ1FX5D1, DZZ0XX0P0, DZZ1XX1B6
 Type of lamps used : LED
 Grease filter type : Kassette
 Clean filter reminders : No
 Connection Rating : 255 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : Gardy plug w/ earthing
 Installation typology : Wall-mounted
 Material body : Stainless steel
 Plug type : Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in) : x x
 Dimensions of the packed product : 19.29 x 25.59 x 40.55
 Net weight : 31.000 lbs
 Gross weight : 42.000 lbs
 Motor location : Integrated motor in hood chimney
 No-return airflow flap : Yes
 Length electrical supply cord : 130 cm
 Dimensions of the product, with chimney (if exists) : 490 x 900 x 500.0 mm
 Dimensions of the packed product (HxWxD) : 490x650x1030 mm
 Net weight : 13.9 kg
 Gross weight : 19.1 kg



4 242005 039616

Series 4, Wall-mounted cooker hood, 90 cm, Stainless steel DWB97IM50

Box-design hood: performance and matching kitchen design bundled in one hood.

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 62.5 kWh/year
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 52/65 dB

Variant

Design

Technical information

Performance

Power:

Environment and safety:

Comfort

Measures:

Technical information


- Wall Hood Brushed steel
- 90 cm Chimney hood, Brushed steel
- 90 cm Chimney hood
- 90 cm wide
- Suitable for ducted or re-circulated extraction
- For recirculated extraction standard recirculation kit or Clean Air Plus recirculation kit (accessory) needed
- Wall mounted hood
- TouchControl
- Electronic controls
- Electronic control via touch control
- TouchControl with Electronic display
- 3 speeds plus intensive setting via TouchControl
- Electronic controls via TouchControl with Electronic display
- TouchControl (3 speeds plus intensive setting) with Electronic display
- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- Twin channel high performance fan motor
- Energy efficient Capacitor motor
- 2 x 1,5 W LED
- Light Intensity: 214 lux
- Colour Temperature: 3500 K
- Stainless steel filter covers, dishwasher safe
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 Ø 15 cm: max. Normal use 453 m³/h Intensive 739 m³/h
- Extraction rate exhaust air according to EN 61591 max. 739 m³/h
- Extraction rate according to EN 61591 Ø 15 cm: max. Normal use 453 m³/h Intensive 739 m³/h
- Extraction rate exhaust air according to EN 61591: max. normal use 453 m³/h, intensive 739 m³/h
- Noise level according to EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW dB(A) re 1 pW
- Noise level according to EN 60704-2-13 exhaust air: Max. normal use: 65 dB(A) re 1 pW Intensive: 74 dB(A) re 1 pW
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 739 m³/h
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 500 mm
- Dimensions recirculating with CleanAir Plus recirculation kit (HxWxD):
703 x 900 x 500mm - mounting with outer chimney
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Dimensions recirculating with cleanAir Plus recirculation kit (HxWxD);
703 x 900 x 500mm - mounting with outer chimney
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Dimensions recirculating with CleanAir Plus recirculation kit (HxWxD): 703 x 900 x 500 mm - mounting with outer chimney

833-1163 x 900 x 500 mm - mounting with telescopic chimney 703
x 900 x 500 mm - mounting with outer chimney 833 - 1163 x 900 x
500 mm - mounting with telescopic chimney


- Power rating 255 W
- Electrical cable length 1.3 m
- With the Clean Air Plus recirculation kit (available as optional
accessory) your appliances reaches:
Extraction rate in recirculation mode:
Max. normal use: 404m³/h
Intensive: 499m³/h
Noise level in recirculation mode:
Max. normal use: 72dB(A) re 1 pW
Intensive: 76 dB(A) re 1 pW

In accordance with the EU-Regulation No 65/2014


Series 4, Wall-mounted cooker hood, 90 cm, Stainless steel DWB97IM50



Measurements in mm




Measurements in mm



A: Electric

B: Gas - from upper edge of pan support

C: Electric - for Australia and New Zealand



- A: Exhaust air outlet
- B: Socket
- C: Electric
- D: Gas - from upper edge of pan support
- E: Electric - for Australia and New Zealand