

**Series 6, Wall-mounted cooker hood,
90 cm, Black glass canopy
DWK97JQ60B**



**Inclined hood: optimal for keeping an eye
on your pots and pans.**

- **PerfectAir sensor:** enjoy quieter, odour-free cooking.
- **DirectSelect Control:** direct selection of desired settings and light.
- **Extra silent:** the high-performance hood, with minimal noise.
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.

- DWZ0AK0R0 Long Life recirculation kit (chimless)
- DWZ0AK0S0 Long Life recirculation kit
- DWZ0AX5K0 Chimney extension 1000 mm
- DWZ0AX5L0 Chimney extension 1500 mm
- DWZ1AK1B6 Clean Air Plus odor filter (replacement)
- DWZ1AK1I6 Clean Air Plus recirculation kit
- DWZ1AK1V6 Clean Air Plus recirc. kit (chimless)
- DWZ1AX5C6 Clean Air Plus recirc. kit external
- DWZ1AX6E1 Chimney standard black
- DZZ0XX0P0 Long Life odor filter (replacement)
- DZZ1XX1B6 Clean Air Plus odor filter (replacement)

Typology:Wall-mounted
 Length electrical supply cord: 130.0 cm
 Height of product, without chimney: 323 mm
 Net weight: 23.2 kg
 Type of control:Electronic
 Number of speed settings:3-stage + 2 intensive
 Max. air extraction: 431 m³/h
 Boost position output recirculating: 441 m³/h
 Max. air recirculation: 355 m³/h
 Boost position air extraction: 714 m³/h
 Number of lights: 2
 Noise level: 53 dB(A) re 1 pW
 Diameter of air outlet: 120 / 150 mm
 Grease filter material:Washable aluminium
 Odour filter: No
 Operating Mode:Exhaust / Recirculation (Accessory available separately)
 Optional accessories: DWZ0AK0R0, DWZ0AK0S0, DWZ0AX5K0, DWZ0AX5L0, DWZ1AK1B6, DWZ1AK1I6, DWZ1AK1V6, DWZ1AX5C6, DWZ1AX6E1, DZZ0XX0P0, DZZ1XX1B6
 Type of lamps used: LED
 Grease filter type:Kassette
 Clean filter reminders:Yes
 Connection rating: 143 W
 Fuse protection:10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type:GB plug
 Installation typology:Wall-mounted
 Material body:Glass, Lacquered
 Plug type:GB plug
 Dimensions of the product, with chimney (if exists) (in):x x
 Dimensions of the packed product: 27.16 x 29.13 x 40.94
 Net weight: 51.000 lbs
 Gross weight: 70.000 lbs
 Motor location: Integrated motor in hood body
 No-return airflow flap: No
 Length electrical supply cord: 130.0 cm
 Dimensions of the product, with chimney (if exists): 452 x 890.0 x 499.0 mm
 Dimensions of the packed product (HxWxD): ... 690 x 740 x 1040 mm
 Net weight: 23.2 kg
 Gross weight: 31.9 kg



Series 6, Wall-mounted cooker hood, 90 cm, Black glass canopy DWK97JQ60B

Inclined hood: optimal for keeping an eye on your pots and pans.

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 34.6 kWh/year
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 45/53 dB

Variant

Design

Technical information

Performance

Power:

Environment and safety:

Comfort

Measures:

Technical information

- Inclined Hood black
- 90 cm
- 89 cm Chimney hood, black
- Glass plate: Clear glass black printed.
- Suitable for ducted or re-circulated extraction
- In recirculation operation chimless use possible
- Wall mounted hood
- easy wall fixing system
- PowerBoost position
- For recirculated extraction a standard recirculation kit or a Clean Air recirculation kit (accessory) is needed
- TouchControl
- Electronic controls
- TouchControl with lightline
- 3 speeds plus 2 intensive via TouchControl
- Electronic controls via TouchControl with lightline
- TouchControl (3 speeds plus 2 intensive) with lightline
- 3 speeds plus 2 intensive
- Automatic 10 minutes after running
- 2 capture areas: front side and bottom side
- Automatic revert setting, 6 minutes
- easy to clean innerframe
- Air quality sensor
- Light dimmer function
- SoftLight
- Twin channel high performance fan motor
- Efficient BLDC-technology
- 2 x 1,5 W LED
- Light Intensity: 238 lux

- Colour Temperature: 3500 K
- RimVentilation
- Saturation indicator for grease fliter and odor fliter
- Fliter cover glass
- Metal grease fliter, dishwasher safe
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 431 m³/h Intensive 714 m³/h
- Extraction rate exhaust air according to EN 61591 max.714 m³/h
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 431 m³/h Intensive 714 m³/h
- Extraction rate exhaust air according to EN 61591:
- max. normal use431 m³/h, intensive 714 m³/h
- Noise level according to EN 60704-2-13 at max.normal use exhaust air: 64 dB(A) re 1 pW dB(A)re 1 pW
- Noise level according to EN 60704-2-13 exhaust air: Max.normal use: 53 dB(A)re 1 pWIntensive: 65 dB(A)re 1 pW
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions recirculating with CleanAir Plus recirculation kit(HxWxD):1118 x 890 x 499 mm - mounting with outer chimney 1188-1458 x 890 x 499 mm - mounting with telescopic chimney
- Max.extraction rate:714 m³/h
- Power rating: 143 W
- Dimensions exhaust air (HxWxD): 928-1198 x 890 x 499 mm
- Dimensions recirculating, chimney (HxWxD): 988-1258 x 890 x 499mm
- Dimensions recirculating, chimless (HxWxD): 452 mm x 890 x 499 mm
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use:410m³/h
- Intensive:632m³/h
- Noise level in recirculation mode with Clean Air Plus odor filter : Max. normal use:63dB(A) re 1 pW
- Intensive:74dB(A) re 1 pW

In accordance with the EU-Regulation No 65/2014

