

**Series 4, wall-mounted cooker hood,
60 cm, clear glass
DWA06E652**



**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom in
your kitchen planning.**

- **Silent:** maximal extractor performance with little noise
- **Grease filtration level:** filters out over 85% of the grease from kitchen air
- **LED-Illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- **Intensive speed setting:** removes strong kitchen odours especially quickly and effectively.
- With exhaust, the air is cleaned by a grease filter and then ducted to the outside which ensures optimal kitchen air quality.

Technical data

Typology : Wall-mounted
 Approval certificates : CE, Eurasian, VDE
 Length electrical supply cord : 130 cm
 Net weight : 13.6 kg
 Type of control : Electronic
 : 480 m³/h
 Boost position output recirculating : 272.0 m³/h
 : 272 m³/h
 Boost position air extraction : 625 m³/h
 Number of lights : 2
 : 65 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable aluminium
 Odour filter : No
 Delay Shut off modes : 20 min
 Optional accessories : DHZ5585
 Total power of the lamps : 4 W
 Grease filter type : Kasette
 : 254 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50 Hz
 Plug type : Gardy plug w/ earthing
 Installation typology : Wall-mounted
 Material body : Glass, Stainless steel
 Approval certificates : CE, Eurasian, VDE
 Plug type : Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product : 22.83 x 16.92 x 26.37
 Net weight : 30.000 lbs
 Gross weight : 38.000 lbs
 Motor location : Integrated motor in hood chimney
 No-return airflow flap : Yes
 Length electrical supply cord : 130 cm
 Dimensions of the product, with chimney (if exists) : 687-1097 x
 600.0 x 450.0 mm
 Dimensions of the packed product (HxWxD) : 580 x 430 x 670
 mm
 Net weight : 13.6 kg
 Gross weight : 17.2 kg



4 242005 126408

Series 4, wall-mounted cooker hood, 60 cm, clear glass DWA06E652

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

Design:

- Chimney hood
- Glass design
- Glass plate clear glass
- brushed steel with glass canopy

Environment and safety:

- Energy Efficiency Class: C*
- Average Energy Consumption: 110.7 kWh/year*
- Blower Efficiency Class: D*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Noise min./max. Normal Level: 48/65 dB*

Comfort:

- Wall mounted hood
- Electronic controls via Push button controls with digital display
- Saturation indicator for metal and charcoal filter

Operating and power:

- 3 speeds plus intensive setting
- Max. extraction rate: 625 m³/h

Power:

- Power rating: 254 W
- Twin channel high performance fan motor
- Light Intensity: 381 lux

Measures:

- 60 cm wide
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 687 - 1097 x 600 x 450 mm
- Dimensions recirculating (HxWxD): 687-1097 x 600 x 450 mm

Technical information:

- 2 x 20 W LED
- Colour Temperature: 3500 K
- Suitable for ducted or re-circulated extraction
- For recirculated extraction recirculating kit (accessory) needed
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 Ø 15 cm:
max. Normal use 480 m³/h
Intensive 625 m³/h
- Extraction rate exhaust air according to EN 61591:
max. normal use 480 m³/h, intensive 625 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
Max. normal use: 65 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure)
Intensive: 71 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)
- Extraction rate in recirculation mode:
Max. normal use: 256 m³/h
Intensive: 272 m³/h

** In accordance with the EU-Regulation No 65/2014*

**Series 4, wall-mounted cooker hood, 60 cm,
clear glass
DWA06E652**

