

**Series 2, wall-mounted cooker hood,  
90 cm, Stainless steel  
DWB94BC52**



**Box-design hood: performance and  
matching kitchen design bundled in one  
hood.**

- **Silent:** maximal extractor performance with little noise
- **Grease filtration level:** filters out over 85% of the grease from kitchen air
- **LED-illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- With exhaust, the air is cleaned by a grease filter and then ducted to the outside which ensures optimal kitchen air quality.
- Metal grease filter creates a consistently fresh feel-good ambiance before, during and after cooking

**Technical data**

Typology : Wall-mounted  
 Approval certificates : CE, Eurasian, Morocco, Ukraine, VDE  
 Length electrical supply cord : 130 cm  
 Height of the chimney : 583-912/583-1022 mm  
 Height of product, without chimney : 53 mm  
 Net weight : 11.8 kg  
 Type of control : mechanical  
 Number of speed settings : 3  
 : 365 m<sup>3</sup>/h  
 : 240 m<sup>3</sup>/h  
 Number of lights : 2  
 : 64 dB(A) re 1 pW  
 Diameter of air outlet : 120 / 150 mm  
 Grease filter material : Washable aluminium  
 Odour filter : No  
 Optional accessories : DHZ1225, DHZ1235, DHZ9550,  
 DHZ9551, DWZ1FX5C6, DWZ1FX5D1, DZZ0XX0P0, DZZ1XX1B6,  
 DWZ0DX0A0, DWZ0DX0U0, DWZ0XX0J0, DWZ1DX1B4,  
 DWZ1DX1I4, DWZ1DX1I6  
 Type of lamps used : LED  
 Grease filter type : Kasette  
 : 100 W  
 Fuse protection : 10 A  
 Voltage : 220-240 V  
 Frequency : 50; 60 Hz  
 Plug type : Gardy plug w/ earthing  
 Installation typology : Wall-mounted  
 Material body : Stainless steel  
 Approval certificates : CE, Eurasian, Morocco, Ukraine, VDE  
 Plug type : Gardy plug w/ earthing  
 Dimensions of the product, with chimney (if exists) (in) : / x x  
 Dimensions of the packed product : 19.29 x 25.59 x 40.55  
 Net weight : 26.000 lbs  
 Gross weight : 38.000 lbs  
 Motor location : Integrated motor in hood chimney  
 No-return airflow flap : No  
 Length electrical supply cord : 130 cm  
 Dimensions of the product, with chimney (if exists) : 635-1075  
 MM x 900.0 x 500.0 mm  
 Dimensions of the packed product (HxWxD) : 490 x 650 x 1030  
 mm  
 Net weight : 11.8 kg  
 Gross weight : 17.1 kg



4 242005 053001

## Series 2, wall-mounted cooker hood, 90 cm, Stainless steel DWB94BC52

### Box-design hood: performance and matching kitchen design bundled in one hood.

#### Design:

- Wall mounted hood
- Box design
- Appliance colour: brushed steel

#### Environment and safety:

- Energy Efficiency Class: D\*
- Average Energy Consumption: 53.1 kWh/year\*
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Noise min./max. Normal Level: 49/64 dB\*

#### Comfort:

- push buttons for extractor speeds and light

#### Power:

- Power rating: 100 W
- 3 speeds via push buttons
- 2 x 1,5W LED
- Light Intensity: 91 lux
- Colour Temperature: 3500 K
- Max. extraction rate: 365 m<sup>3</sup>/h

#### Measures:

- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 MM x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 MM x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 900 x 500mm - mounting with outer chimney  
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Dimensions recirculating with CleanAir module (HxWxD);  
703 x 900 x 500mm - mounting with outer chimney  
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 900 x 500mm - mounting with outer chimney  
833-1163 x 900 x 500 mm - mounting with telescopic chimney

#### Technical information:

- Twin channel high performance fan motor
- Suitable for ducted or re-circulated extraction
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate exhaust air according to EN 61591 max. 365 m<sup>3</sup>/h
- Maximum extraction rate exhaust air 365 m<sup>3</sup>/h according to EN 61591
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure)
- Extraction rate in recirculation mode:  
Max. normal use:193 m<sup>3</sup>/h
- Noise level in recirculation mode:  
Max. normal use:66 dB(A) re 1 pW (53 dB(A) re 20 µPa sound pressure)
- Metal grease filter, dishwasher safe
- Electrical cable length 1.3 m

\* In accordance with the EU-Regulation No 65/2014

**Series 2, wall-mounted cooker hood, 90 cm,  
Stainless steel  
DWB94BC52**

