

**Serie | 2, Built-in Extractor Hood, 60 cm, Stainless steel
DHU635GZA**

E



The built-under cooker hood: save space by mounting the hood beneath your upper cabinet or on the wall.

- **Extraction rate:** at 310 m³/h, it quickly ensures optimal kitchen air quality.
- **Halogen lighting:** for optimal, energy-efficient illumination of the hob.
- **Especially quiet:** high performance at just 60 dB.

Technical data

Typology :	Traditional
Approval certificates :	Morocco
Length electrical supply cord (cm) :	130
Net weight (kg) :	7.838
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m ³ /h) :	310
Number of lights :	2
Noise level (dB(A) re 1 pW) :	74
Diameter of air outlet (mm) :	100
Grease filter material :	Washable aluminium
Odour filter :	Yes
Operating Mode :	Convertible
Optional accessories :	DHZ2801
Type of lamps used :	Halogen
Total power of the lamps (W) :	56
Grease filter type :	Multilayer
Connection Rating (W) :	340
Voltage (V) :	230-240
Frequency (Hz) :	50
Plug type :	Gardy plug w/ earthing
Installation typology :	Built-under
Approval certificates :	Morocco
Plug type :	Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	21.45 x 6.88 x 25.19
Net weight (lbs) :	17
Gross weight (lbs) :	20
Motor location :	N/A
No-return airflow flap :	Yes
Length electrical supply cord (cm) :	130
Dimensions of the product, with chimney (if exists) (mm) :	135 x 600.0 x 495.0
Dimensions of the packed product (HxWxD) (mm) :	545 x 175 x 640
Net weight (kg) :	7.838
Gross weight (kg) :	9.0



**Serie | 2, Built-in Extractor Hood, 60 cm,
Stainless steel
DHU635GZA**

**The built-under cooker hood: save space
by mounting the hood beneath your upper
cabinet or on the wall.**

Comfort and Safety:

- 3 speed operation
- Charcoal cassette filter
- Twin motor

Design:

- Slimline conventional hood
- For installation underneath a wall cupboard or on the wall
- Suitable for ducted or re-circulated extraction