


**Serie | 6, Freestanding Fridge-freezer
(Bottom freezer), 186 x 70 cm,
KGN46AI30Z**



Included accessories

2 x cold accumulator
3 x egg tray
1 x bottle holder in door tray

- **XL size:** provides lots of space for your food.
- **Perfect Fit:** The appliance can be positioned right next to side walls and furniture - flexible installation possible
- **LED light:** illuminates the refrigerator evenly without glare, for the life of the appliance.
- **VarioZone:** more flexibility due to variable-use glass shelves and drawers in the freezer compartment.
- **NoFrost:** never defrost again, thanks to perfect protection from ice formation - that saves time and effort.

Technical data

Built-in / Free-standing :	Free-standing
Number of compressors :	1
Number of independent cooling systems :	2
Width of the appliance :	700
Depth of the product :	670
Net weight (kg) :	86.527
Door panel options :	Not possible
Door hinge :	Right reversible
Number of Adjustable Shelves in fridge compartment :	3
Shelves for Bottles :	No
Frost free system :	Fridge and freezer
Interior ventilator :	No
Reversible Door Hinge :	Yes
Length electrical supply cord (cm) :	240
Noise level (dB(A) re 1 pW) :	40
Multi-Flow Air Tower :	Yes
Fast cooling switch :	Yes
Fast freezing switch :	No
Temperature Controlled Drawer :	No
Humidity Control Drawer :	Yes
Number of Door Bins - Refrigerator :	2
Door bin adjustability - Refrigerator :	No
Tilt-out door bins in fridge :	Yes
Gallon Storage :	Yes
Number of Gallon storage :	1
Motorized Shelf :	No
Door opened indicator freezer :	Yes
Automatic motor-driven ice-maker :	No
Connection Rating (W) :	100
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50
Storage Period in Event of Power Failure (h) :	20
Approval certificates :	CE, VDE
Door panel options :	Not possible
Noise level (dB(A) re 1 pW) :	40
Energy Star Qualified :	No
Approval certificates :	CE, VDE
Plug type :	South Africa plug
Required cutout/niche size for installation (in) :	x x
Dimensions of the packed product (in) :	74.80 x 29.52 x 29.13
Net weight (lbs) :	191.000
Gross weight (lbs) :	195.000



Serie | 6, Freestanding Fridge-freezer (Bottom freezer), 186 x 70 cm, KGN46AI30Z

Consumption

- Energy efficiency class: A++
- Energy efficiency class: A++ (288 kWh per year). Actual energy consumption will depend on how the appliance is used and where it is located.
- Total net capacity: 385 litres
- Noise level dB(A) re 1 pW: 40

Design

- Doors inox EasyClean, side panels Steel Look
- LED with Soft Start in fridge section

Comfort and Safety

- Frost free - never again defrosting
- External In-Door LCD Electronics
- Supercool function
- Superfreeze Function
- Optical and acoustic warning system

Fridge Section

- Net capacity refrigeration zone: 280 l
- Multi Airflow-System
- without

Freshness System

Freezer Section

- Net freezer capacity 105 litres
- Freezing capacity: 15 kg in 24 hours
- Storage time in power failure: 20 Hours

APPLIANCE DIMENSION

- Dimensions: H 186 cm x L 70 cm x D 67 cm

TECHNICAL INFORMATION

- Door right hinged, reversible
- Height adjustable front feet, roles in the back
- Climate Class SN-T
- Connected load 100 W
- Rated Voltage 220 - 240 V


Standard Accessories

- 3 x egg tray, 2 x cold accumulator, 1 x bottle holder in door tray

Country Specific Options

- Gross capacity, total: 415 l
- Gross capacity cooling 287 l
- **** freezer 128 l (-18°C and below)
- Based on the results of the standard 25-hour test. Actual consumption depends on usage/position of the appliance.

Serie | 6, Freestanding Fridge-freezer (Bottom freezer), 186 x 70 cm, KGN46AI30Z



Appliance name	a	b	c	d	e	f	g	h
KGN 46 (Outer handle)	1860	700	670	590	740	1310	710	12
KGN 46 (Inner handle)	1860	700	670	590	710	1310	670	12
KGN 49 (Outer handle)	2030	700	670	590	740	1310	710	12
KGN 49 (Inner handle)	2030	700	670	590	710	1310	670	12

Description

a Height

b Width

c Depth with door closed, without handle

d Cabinet depth

e Width with door opened to 90°

f Depth with door opened, without handle

g Depth with door closed, with handle

h Air gap for installation in recess or fixed cabinet

measurements in mm