


Series 6, Gas Hob, 60 cm, Tempered glass, Black PPP6A6B20Z





HEZ298105 Simmer plate HEZ298114 Small pot support

The tempered-glass gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

- FlameSelect: for a precise adjustment of the flame in nine defined levels
- Single cast-iron pan supports: for high firmness and easy handling.
- Sword knobs: for an ergonomic control.
- Surface colour: elegant black tempered-glass design.
- Standard and semi-flush built-in option: choose between flush or slightly raised installation.

Product name/family:gas hob w integrated controls Built-in / Free-standing:
Type of control setting devices: sword knobs
Min. required niche size for installation (HxWxD):45 x 560-562 x
480-492 mm
Width of the appliance:
Dimensions:
Dimensions of the packed product (HxWxD): 141 x 651 x 578 mm
Net weight:
Gross weight: 15.0 kg
Residual heat indicator:No
Location of control panel: Front
Basic surface material: Tempered glass
Color of surface:Black
Color of frame:Black
Length electrical supply cord:
EAN code:
Gas connection rating:7500 W
Fuse protection:3 A
Voltage:
Frequency: 50-60 Hz





Series 6, Gas Hob, 60 cm, Tempered glass, Black PPP6A6B20Z

The tempered-glass gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

Design

- tempered black hard glass base surface, black
- frameless: install the hob either flush or slightly raised on the worktop
- Cast iron w rubber feet single

Comfort & Convenience

- Step valve 9 steps: precisely adjust the flame in nine defined and repeatable levels.
- Sword Knobs: easily access knobs in front with strong grip for effortless turning.
- Ignition via control knobs: just push and turn the knob to ignite the flame.

Burners and power

- 4 PC
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Liquid gas G30,31 28-30/37mbar
- Preset of liquid gas (28-30/37mbar)
- Dimensions of the product (HxWxD mm): 58 x 590 x 520
- Required niche size for installation (HxWxD mm) : $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord 1 m South Africa plug: plug and play, no electrician required for installation.
- Connected load: 7.5 KW



Series 6, Gas Hob, 60 cm, Tempered glass, Black PPP6A6B20Z

